

# SERIES 1167/ 1168

## ATHLETIC LINE MARKING PAINT

### DELUXE



#### **PRODUCT FEATURES**

- Quick dry
- Weather resistant- Premium quality
- Custom colors upon request
- Soap & water clean- up
- For grass, synthetic turf & black top

#### **GENERAL PROPERTIES**

A heavy duty, exterior, vinyl-acrylic latex line marking paint. Dries within a 1/2 hour to a tough, durable weather resistant finish.

#### **RECOMMENDED USES**

- Natural field turf
- Synthetic field turf
- Black top

#### **LIMITATIONS**

- Do not apply at temperatures less than 45°F.

<b>Finish</b>	Flat
<b>Vehicle Type</b>	Vinyl- Acrylic
<b>Pigment Type</b>	Titanium Dioxide
<b>Solvent Type</b>	Water
<b>Coating Category</b>	Flat coating VOC < 50 g/l
<b>% Solid by Weight</b>	39% minimum
<b>% Solid by Volume</b>	22% minimum
<b>Weight/Per Gallon</b>	10.25 lbs / gal minimum
<b>Recommended Dry Film by Coat</b>	5-8 mils per coat
<b>Theoretical Coverage</b>	3 inch line- 650 lineal ft/ gal
<b>Viscosity @ 77° F</b>	90 KU minimum
<b>Dry Time Average</b>	15-20 minutes
<b>Application Method</b>	Stripping equipment
<b>Shelf Life</b>	2 Years
<b>Packaged</b>	Five gallon pails only
<b>Flash Point</b>	N/A
<b>Colors</b>	White, yellow, blue, red, orange, green, pink
<b>Federal Specification</b>	Proprietary



### **SURFACE PREPARATION**

All surfaces to be clean and dry.

### **APPLICATION CONDITIONS**

Minimum temperature: 45°F

### **APPLICATION EQUIPMENT**

Spray- Stripping equipment

### **THINNING / CLEAN UP INSTRUCTIONS**

1 gallon of water to 1 gallon of Line Marking Paint.

### **ENVIRONMENTAL INFORMATION**

Meets or exceeds the criteria set forth by the U.S. Green buildings Council LEED-CI, version 2.0 and LEED-NC version 2.2. Contains no lead, mercury, or chromate hazardous compounds. Complies with N.Y., N.J., and other states' requirements for limitation of volatile organic compounds. Meets New York Part 205 architectural surface coatings. Meets criteria for non- photochemical solvents in accordance with New York City Law 49.

Keep out of reach of children.

Material Safety Data Sheets available upon request.

Protect from freezing.

### **HEALTH & SAFETY INFORMATION**

Use only with adequate ventilation. Do not breathe vapors, spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves.

### **ACCURACY OF DATA**

The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit [www.mercurypaint.com](http://www.mercurypaint.com) for the newest version of this data sheet.

### **WARRANTY**

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor of other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.

