

SERIES 8900

EVERFRESH LATEX SEMI-GLOSS FINISH- ZERO VOC



PRODUCT FEATURES

- Zero VOC
- Low odor
- Durable
- Hi-hiding
- Quick return to service
- Meets LEED-CI, version 2.0
- Meets LEED-NC, version 2.2
- EPA test method 24 VOC <150 g/l
- Washable

GENERAL PROPERTIES

A low odor, zero VOC latex semi-gloss finish. This washable finish meets LEED-CI, version 2.0 and LEED-NC, version 2.2. An excellent coating that helps facilitate quick return to service.

RECOMMENDED USES

- Walls & Ceilings
- Sheetrock
- Plaster
- Masonry
- Primed wood & metal
- Residential & schools
- Hospitals & institutions
- Facility management

LIMITATIONS

- Do not apply when air and surface temperature are below 50°F.
- Tinting may increase the VOC.

Finish	Semi-gloss
Vehicle Type	100% Acrylic
Pigment Type	Titanium Dioxide
Solvent Type	Water
Coating Category	Zero
% Solid by Weight	59% minimum
% Solid by Volume	44% minimum
Weight/Per Gallon	11.30 +/- 0.30 lbs/gal max
Recommended Dry Film by Coat	1.5 to 2.5 mils per coat
Theoretical Coverage	400-450 sq ft. / gallon
Viscosity @ 77° F	90-95 KU
Dry Time Average	To touch: 1 hour To recoat: 4 hours
Application Method	Brush, roller, spray
Shelf Life	2 Years
Packaged	One, two and five gallon pails
Flash Point	N/A
Colors	White and custom colors upon request
Federal Specification	Proprietary



SURFACE PREPARATION

All surfaces must be dry, thoroughly clean, free of loose paint, rust, grease, oil and all other foreign matter.

APPLICATION CONDITIONS

Do not apply over moisture or wet surfaces.
 Air and surface temperatures must be above 50°F.

APPLICATION EQUIPMENT

Brush – Use finest quality nylon or bristle brush.
 Roller –1/4-3/8 nap- smooth surface
 3/4- 1 1/4 nap- rough surface
 Spray – Fluid pressure: 1,500-2,000 PSI
 Tip: 0.18 orifice.

THINNING / CLEAN UP INSTRUCTIONS

Do not thin. Use as supplied. Do not add paint or solvent.

ENVIRONMENTAL INFORMATION

Meets or exceeds the criteria set forth by the U.S. Green building council LEED-CI, version 2.0 and LEED-NC, version 2.2. Contains no lead, mercury or chromate hazardous compounds. Complies with NY, NJ and other states' requirements for limitation of volatile organic compounds. Meets New York Part 205 architectural surface coatings. Meets criteria for non-photochemical solvents in accordance with New York City Law 49.

Keep out of reach of children.
Safety Data Sheets available upon request.
Keep from freezing.

HEALTH & SAFETY INFORMATION

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves during application or sanding. A dust particulate respirator approved by NIOSH should be worn when sanding or spraying. Close container after each use.

RECOMMENDED SYSTEMS

Plaster/ Drywall New & Repainted	Primer: Series 5900 Everfresh Finish: Series 8900 Latex Semi-Gloss
Wood New/ Repainted	Primer: Series 5900 Everfresh Finish: Series 8900 Latex Semi-Gloss
Masonry New/ Repainted	Primer: Series 5900 Everfresh Finish: Series 8900 Latex Semi-Gloss
Ferrous Metal New/ Repainted	Primer: Series 3000 Metal Primer Finish: Series 8900 Latex Semi-Gloss
Galvanized Metal New/ Repainted	Primer: Series 2100 Latex Metal Primer Finish: Series 8900 Latex Semi-Gloss

ACCURACY OF DATA

The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit www.mercurypaint.com for the newest version of this data sheet.

WARRANTY

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor of other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.

