

SERIES 6600

HIGH GLOSS POLYURETHANE FINISH



PRODUCT FEATURES

- Super tough finish
- VOC compliant
- Gloss finish
- Resistant to heavy traffic
- Resistant to cleaning compounds
- Easy to apply

GENERAL PROPERTIES

A heavy duty VOC compliant, oil-modified polyurethane, clear gloss coating. Dries to a super tough finish that is resistant to: heavy traffic, abrasion, rubber burns and cleaning compounds.

RECOMMENDED USES

- Wood
- Floors
- Railings
- Concrete
- Gym floors
- Metal
- Boats
- Trim
- Furniture
- Decks
- Benches

LIMITATIONS

- Do not apply when air and surface temperature are below 40°F.

Finish	Gloss
Vehicle Type	Oil- modified polyurethane
Pigment Type	N/A
Solvent Type	Mineral spirits
Coating Category	350 g/l (max) VOC
% Solid by Weight	60% minimum
% Solid by Volume	55% minimum
Weight/Per Gallon	7.70 lbs/ gal minimum
Recommended Dry Film by Coat	1.5 to 2 mils per coat
Theoretical Coverage	850 sq ft. / gallon
Viscosity @ 77° F	N/A
Dry Time Average	To touch: 3 hours
Application Method	Brush, roller, spray
Shelf Life	2 Years
Packaged	One and five gallon pails
Flash Point	Above 100°F
Colors	N/A
Federal Specification	TT-V-71H



SURFACE PREPARATION

All surfaces must be dry, thoroughly clean, free of loose paint, rust, dirt, oil, grease and all other foreign matter.

APPLICATION CONDITIONS

Do not apply over moisture or wet surfaces.
Air and surface temperature must be above 90°F.

APPLICATION EQUIPMENT

Brush – Any good quality will suffice
Roller – Any good quality will suffice
Spray – Airless spray

THINNING / CLEAN UP INSTRUCTIONS

Thinning not normally required. If necessary use mineral spirits.

ENVIRONMENTAL INFORMATION

Contains no lead, mercury or chromate hazardous compounds. Complies with N.Y., N.J. and other states' requirements for limitation of volatile organic compounds. Meets New York Part 205 architectural surface coatings. Meets criteria for non-photochemical solvents in accordance with New York City Law 49.

Keep out of reach of children.
Safety Data Sheets available upon request.
Keep from freezing.

HEALTH & SAFETY INFORMATION

Contains mineral spirits. Keep away from heat and open flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHATC23C or equivalent), or leave the area. Close container after each use. Avoid prolonged contact with skin. Do not take internally.

RECOMMENDED SYSTEMS

Wood New	Primer: Series 6600 Finish: Series 6600
Wood Repainted	Primer: Series 6600 Finish: Series 6600
Masonry New	Primer: Series 6600 Finish: Series 6600
Masonry Repainted	Primer: Series 6600 Finish: Series 6600
Ferrous Metal New	Primer: Series 6600 Finish: Series 6600
Ferrous metal Repainted	Primer: Series 6600 Finish: Series 6600

ACCURACY OF DATA

The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit www.mercurypaint.com for the newest version of this data sheet.

WARRANTY

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor of other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.

