

SAFETY DATA SHEET



Issuing Date No data available

Revision Date 25-Jun-2015

■ COLORWORKS:

Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name

SERIES 6200 ZOOM SURE GRIP FLOOR COATING

Other means of identification

Synonyms

None

Recommended use of the chemical and restrictions on use

Recommended Use

Paint, Latex

Uses advised against

No information available

Details of the supplier of the safety data sheet

Supplier Name

MERCURY PAINT

Supplier Address

4808 FARRAGUT ROAD

BROOKLYN

NY 11203 US

Supplier Phone Number

Phone:7184698787 Fax:7184698787

Supplier Email

VGANDHI@MERCURYPAINT.COM

Emergency telephone number

Company Emergency Phone

Number

CHEMTREC18004249300

2. HAZARDS IDENTIFICATION

Classification



This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Flammable liquids	Category 4

GHS Label elements, including precautionary statements

Emergency Overview

Signal word

Warning

Hazard Statements

Suspected of causing cancer
Suspected of damaging fertility or the unborn child
Combustible liquid



Appearance White & Multiple Colors

Physical state Liquid

Odor No data available

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable



Unknown Toxicity

Not applicable

Other information

Harmful to aquatic life with long lasting effects PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Titanium dioxide	13463-67-7	10-30	*
Diethylene glycol monomethyl ether	111-77-3	1 - 5	*
2-Propanol, 1-(2-butoxy-1-methylethoxy)-	29911-28-2	1 - 5	*
Polyethylene glycol branched nonylphenyl ether	68412-54-4	0.1 - 1	*
Ammonium hydroxide	1336-21-6	0.1 - 1	*
Sodium nitrite	7632-00-0	0.1 – 1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

Eye contact

Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist,

call a physician.

Skin contact

Wash with soap and water.

Inhalation

Remove to fresh air.

Ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth

to an unconscious person.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. Wear personal

protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and No information available.

Effects

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.



Revision Date 25-Jun-2015

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray.

Uniform Fire Code

Combustible Liquid: III-A

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact

No.

Sensitivity to Static Discharge

No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid contact with eyes. Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Take precautionary measures against static discharges. Do not touch or walk through spilled material.

Other Information

Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so. Do not touch or walk through spilled

material. Dike far ahead of liquid spill for later disposal.

Methods for cleaning up

Pick up and transfer to properly labeled containers. Take precautionary measures against

static discharges. Dam up. Soak up with inert absorbent material.

Revision Date 25-Jun-2015

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Do not breathe dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities

Storage

Store locked up. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products

None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Titanium dioxide 13463-67-7	TWA: 10 mg/m³	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³ total dust	IDLH: 5000 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992)

Appropriate engineering controls

Engineering Measures

Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Skin and body protection

Wear protective gloves and protective clothing.

Respiratory protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular

cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state

Liquid

Appearance Color

Multiple Colors White

Odor **Odor Threshold** No data available No information available

Property

Flash Point

Values

Remarks Method

pН Melting / freezing point Boiling point / boiling range 8+ No data available 37:78%°C (>100°F) 93 C / 199 F No data available

None known None known None known None known None known

None known

None known

None known

None known

Evaporation Rate Flammability (solid, gas)

No data available Flammability Limit in Air Upper flammability limit No data available

Lower flammability limit Vapor pressure Vapor density Specific Gravity

No data available No data available No data available

Water Solubility Solubility in other solvents

1.240 Soluble in water No data available Partition coefficient: n-octanol/waterNo data available No data available

None known None known None known None known No data available None known No data available None known

Kinematic viscosity Dynamic viscosity **Explosive properties** Oxidizing properties

Autoignition temperature

Decomposition temperature

No data available No data available No data available None known

Other Information

Softening Point VOC Content (%) Particle Size

No data available 63%(V/V) 50%(v/w) No data available

Particle Size Distribution

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks. Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

Carbon oxides.



11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available.

Eye contact Specific test data for the substance or mixture is not available.

Skin contact Specific test data for the substance or mixture is not available.

Ingestion Specific test data for the substance or mixture is not available.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
2-Propanol, 1-(2-butoxy-1-methylethoxy)- 29911-28-2	= 1620 μL/kg (Rat)	= 5860 μL/kg (Rabbit)	= 42.1 ppm (Rat)4 h
Polyethylene glycol branched nonylphenyl ether 68412-54-4	•	= 1780 μL/kg (Rabbit)	-
Ammonium hydroxide 1336-21-6	= 350 mg/kg (Rat)	-	
Sodium nitrate 7632-00-0	=85 mg/kg (Rat)	-	=5.5 mg/l (Rat) 4 h

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

No information available.

Mutagenic Effects

No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B		X
13463-67-7				
Sodium nitrate 7632-00-0		Group 2A		×

Reproductive toxicity

Contains a known or suspected reproductive toxin.

STOT - single exposure

No information available.

STOT - repeated exposure

No information available.

Chronic Toxicity

No known effect based on information supplied. Contains a known or suspected carcinogen. Contains a known or suspected reproductive toxin. Possible risk of irreversible effects. Titanium dioxide has been classified by the International Agency for Research on Cancer



(IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.

Target Organ Effects

Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Reproductive System.

Aspiration Hazard

No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)21,851.00 mg/kg **ATEmix (dermal)**96,697.30 mg/kg (ATE)

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Diethylene glycol monomethyl ether 111-77-3	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: = 7500 mg/L (Lepomis macrochirus) 96h LC50: = 5741 mg/L (Pimephales promelas)	EC50 > 10000 mg/L 17 h	48h EC50; > 500 mg/L
2-Propanol, 1-(2-butoxy-1-methylethoxy)- 29911-28-2		96h LC50: = 841 mg/L (Poecilia reticulata)		
Ammonium hydroxide 1336-21-6		96h LC50: = 8.2 mg/L (Pimephales promelas)		48h EC50: = 0.66 mg/L
Sodium nitrate 7632-00-0		96h LC50: 0.092-0.13 ,g/L (Oncorhynchus mykiss) 96h LC50: 0.4-0.06 mg/L (Oncorhynchus mykiss) 96h LC50:= 0.65-1 mg/L Oncorhynchus mykiss) 96h LC50:=2.3 mg/L (Pimephales promelas) 96h LC50:=20 mg/L (Pimephales promelas) 96h LC50:=0.19 mg/L (Oncorhynchus mykiss)		

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Diethylene glycol monomethyl ether 111-77-3	-0.682
Sodium nitrate 7632-00-0	-3.7

Other adverse effects

No information available.



13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Ammonium hydroxide	Toxic
1336-21-6	Corrosive
Sodium nitrate	Toxic
7632-00-0	Ignitable
	Reactive

14. TRANSPORT INFORMATION

DOT

NOT REGULATED

Proper Shipping Name

NON REGULATED

Hazard Class

N/A

TDG

Not regulated

MEX

Not regulated

ICAO

Not regulated

ATA

Not regulated

Proper Shipping Name

NON REGULATED

Hazard Class

N/A

IMDG/IMO

Not regulated

Hazard Class

N/A

RID

Not regulated

ADR

Not regulated

ADN

Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA DSL Complies

All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Diethylene glycol monomethyl ether - 111-77-3	111-77-3	1 - 5	1.0
Ammonium hydroxide - 1336-21-6	1336-21-6	0.1 - 1	1.0
Sodium nitrate 7632-00-0	7632-00-0	0.1 – 1	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ammonium hydroxide 1336-21-6	1000 lb			Х
Sodium nitrate 7632-00-0	100 lb			×

<u>CERCLA</u>

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ammonium hydroxid 1336-21-6	e 1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Sodium nitrate 7632-00-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65	
Titanium dioxide - 13463-67-7	Carcinogen	
Formaldehyde - 50-00-0	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Titanium dioxide	X	X	X		



X

13463-67-7					
Diethylene glycol monomethyl ether 111-77-3		×	X	X	X
Ammonium hydroxide 1336-21-6	Х	Х	Х	Х	

International Regulations

Component	Carcinogen Status	Exposure Limits
Titanium dioxide		Mexico: TWA= 10 mg/m ³
13463-67-7 (3 - 7)		Mexico: STEL= 20 mg/m ³

Canada

HMIS

WHMIS Hazard Class

Not determined

16. OTHER INFORMATION

NFPA Health Hazards 2 Flammability 1 Instability 0 Physical and

Health Hazards 2* Flammability 1 Physical Hazard 0 Personal Protection

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110

1-800-572-6501

Revision Date

25-Jun-2015

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet