

ZOOM SERIES 6700

PRIMER-SEALER/ STAIN KILLER



PRODUCT FEATURES

- Quick dry- 20 minutes
- Excellent adhesion
- Blocks stains
- Seals porous surfaces
- Blocks smoke odor
- Seals knots
- Will prime glossy surfaces

GENERAL PROPERTIES

A quick drying, high hiding, stain and odor blocker resulting from fire damage, water damage, rust, crayons, lipstick, graffiti, markers, knots, sap and tannin bleed.

RECOMMENDED USES

- Ceilings
- Walls
- Cabinets
- Furniture
- Graffiti blocker
- Stain blocker
- Smoke damage
- Water damage

LIMITATIONS

- Do not apply over moisture.
- Do not apply to floors and decks.
- Not for immersion service.

Finish	Low Luster
Vehicle Type	Modified Shellac
Pigment Type	Titanium Dioxide
Solvent Type	Alcohol
Coating Category	Primer, Sealer, Undercoater max VOC 200 g/l
% Solid by Weight	80% minimum
% Solid by Volume	61% minimum
Weight/Per Gallon	13.70 +/- 0.50 lbs/gal
Recommended Dry Film by Coat	1.5 to 2 mils per coat
Theoretical Coverage	400-500 sq ft. / gallon
Viscosity @ 77° F	63-75 KU
Dry Time Average	To touch: 20 min To recoat: 40 min
Application Method	Brush, roller, spray
Shelf Life	1 Year
Packaged	One and five gallon pails
Flash Point	61°F
Colors	White and tinted colors upon request
Federal Specification	Proprietary



SURFACE PREPARATION

All surfaces should be clean, dry, sound and free of dust, dirt, excessive chalky material, grime, grease, oil, wax, mildew, wallpaper adhesive or any contamination that may interfere with adhesion.

APPLICATION CONDITIONS

Relative humidity: 70%
Temperature: 30°F-90°F

APPLICATION EQUIPMENT

Brush – Use nylon/ poly or natural bristle brush
Roller – Low nap
Spray – Fluid pressure 800-1,200 PSI
Tip- 0.11-0.13 orifice

THINNING / CLEAN UP INSTRUCTIONS

Do not thin. Clean up with denatured alcohol.

ENVIRONMENTAL INFORMATION

Contains no lead, mercury or chromate hazardous compounds. Complies with N.Y., N.J. and other states' requirements for limitation of volatile organic compounds.

Keep out of reach of children.

Safety Data Sheets available upon request.

Keep from freezing.

HEALTH & SAFETY INFORMATION

WARNING: FLAMMABLE LIQUID AND VAPOR. CONTAINS ETHANOL. Keep away from heat and open flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHATC23C or equivalent), or leave the area. Close container after each use. Avoid prolonged contact with skin. Do not take internally. If swallowed, contact a physician or poison control center. Avoid skin contact.

RECOMMENDED SYSTEMS

Drywall	Primer: Series 6700 Finish: appropriate Mercury Finish Coat
Wood	Primer: Series 6700 Finish: appropriate Mercury Finish Coat
Metal	Primer: Series 6700 Finish: appropriate Mercury Finish Coat
Concrete Block	Primer: Series 6700 Finish: appropriate Mercury Finish Coat
Poured Concrete	Primer: Series 6700 Finish: appropriate Mercury Finish Coat

ACCURACY OF DATA

The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit www.mercurypaint.com for the newest version of this data sheet.

WARRANTY

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor of other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.

