

# SERIES 9150

## EVERFRESH LATEX EGGSHELL FINISH- ZERO VOC



### PRODUCT FEATURES

- Zero VOC
- Low odor
- Durable
- Quick return to service
- Meets LEED-CI, version 2.0
- Meets LEED-NC, version 2.2
- EPA test method 24 VOC <150 g/l
- Washable

### GENERAL PROPERTIES

A low odor, zero VOC latex eggshell finish. This coating meets LEED-CI, version 2.0 and LEED-NC, version 2.2. An excellent coating that helps facilitate quick return to service.

### RECOMMENDED USES

- Walls & ceilings
- Sheetrock
- Plaster
- Masonry
- Primed wood & metal
- Residential & schools
- Hospitals & institutions
- Facility management

### LIMITATIONS

- Do not apply when air and surface temperature are below 50°F.
- Tinting may increase the VOC.

<b>Finish</b>	Eggshell
<b>Vehicle Type</b>	100% Acrylic
<b>Pigment Type</b>	Titanium Dioxide
<b>Solvent Type</b>	Water
<b>Coating Category</b>	Zero
<b>% Solid by Weight</b>	58% minimum
<b>% Solid by Volume</b>	42% minimum
<b>Weight/Per Gallon</b>	11.40 +/- 0.30 lbs/gal
<b>Recommended Dry Film by Coat</b>	1.5 to 2.5 mils per coat
<b>Theoretical Coverage</b>	400-450 sq ft. / gallon
<b>Viscosity @ 77° F</b>	85-95 KU minimum
<b>Dry Time Average</b>	To touch: 1 hour To recoat: 4 hours
<b>Application Method</b>	Brush, roller, spray
<b>Shelf Life</b>	2 Years
<b>Packaged</b>	One, two and five gallon pails
<b>Flash Point</b>	N/A
<b>Colors</b>	White and custom colors upon request
<b>Federal Specification</b>	Proprietary





**SURFACE PREPARATION**

All surfaces must be dry, thoroughly clean, free of loose paint, rust, grease, oil and all other foreign matter.

**APPLICATION CONDITIONS**

Do not apply over moisture or wet surfaces.  
 Air and surface temperatures must be above 50°F.

**APPLICATION EQUIPMENT**

Brush – Use finest quality nylon or bristle brush  
 Roller –1/4-3/8 nap- smooth surface  
           3/4- 1 1/4 nap- rough surface  
 Spray – Fluid pressure 1,500-2,000 PSI  
           Tip- 0.18 orifice

**THINNING / CLEAN UP INSTRUCTIONS**

Do not thin. Use as supplied. Do not add paint or solvent.

**ENVIRONMENTAL INFORMATION**

Meets or exceeds the criteria set forth by the U.S. Green building council LEED-CI, version 2.0 and LEED-NC, version 2.2. Contains no lead, mercury or chromate hazardous compounds. Complies with NY, NJ and other states’ requirements for limitation of volatile organic compounds. Meets New York Part 205 architectural surface coatings. Meets criteria for non-photochemical solvents in accordance with New York City Law 49.

**Keep out of reach of children.**  
**Safety Data Sheets available upon request.**  
**Keep from freezing.**

**HEALTH & SAFETY INFORMATION**

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves during application or sanding. A dust particulate respirator approved by NIOSH should be worn when sanding or spraying. Close container after each use.

**RECOMMENDED SYSTEMS**

<b>Plaster/ Drywall New &amp; Repainted</b>	Primer: Series 5900 Everfresh Finish: Series 9150 Eggshell
<b>Wood New/ Repainted</b>	Primer: Series 5900 Everfresh Finish: Series 9150 Eggshell
<b>Masonry New/ Repainted</b>	Primer: Series 5900 Everfresh Finish: Series 9150 Eggshell
<b>Ferrous Metal New/ Repainted</b>	Primer: Series 3000 Metal Primer Finish: Series 9150 Eggshell
<b>Galvanized Metal New/ Repainted</b>	Primer: Series 2100 Latex Metal Primer Finish: Series 9150 Eggshell

**ACCURACY OF DATA**

The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit [www.mercurypaint.com](http://www.mercurypaint.com) for the newest version of this data sheet.

**WARRANTY**

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor of other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.

