



Mercury Paint SERIES

900A/900B WATERBOURNE EPOXY COATING

PRODUCT FEATURES

- Durable
- Chemical Resistant
- Excellent Gloss Retention
- Excellent Color Retention
- Interior/Exterior
- Low Odor

GENERAL PROPERTIES

A high performance, interior/exterior, low odor waterbourne coating. Dries to a tough, gloss finish which will withstand heavy industrial traffic, abrasion and chemical attack.

RECOMMENDED USES

- Concrete Floor
- Walls
- Plaster
- Rest rooms
- Schools
- Drywall
- Food processing plants
- Power plants
- Factories
- Institutions
- Hospitals

LIMITATIONS

- Not for immersion service.
- 4 Hour pot life

TECHNICAL DATA

Finish	900A - Gloss 900B - Semi-Gloss
Vehicle Type	Waterbourne acrylic/epoxy
Pigment Type	Titanium Dioxide & Light Fast Pigments
Solvent Type	Water
Coating Category	Industrial Maintenance coating VOC 340 g/l max
% Solid by Weight	50% minimum (mixed)
% Solid by Volume	36% minimum (mixed)
Weight/Per Gallon	10.60 avg
Recommended Dry Film by Coat	1.5 to 2 mils per coat
Theoretical Coverage	300-400 sq ft / gallon
Viscosity @ 77° F	90 minimum
Dry Time Average	To touch: 2 hours. To recoat: 12 hours
Application Method	Brush, roller, spray
Shelf Life	2 Years
Packaged	Four gallon kits only 3:1 ratio
Flash Point	200° F
Colors	Custom colors upon request
Federal Specification	Proprietary



Mercury Paint

