

SERIES 6000

ACRYLIC LATEX FLAT FINISH



PRODUCT FEATURES

- Hi-hiding
- Washable
- Low odor
- Self priming
- Soap & water clean up
- Fire retardant ASTM E-84
- Meets LEED-CI, version 2.0
- Meets LEED-NC, version 2.2
- EPA test method 24 VOC <50 g/l

GENERAL PROPERTIES

A quality acrylic latex paint that is easy to apply, has excellent hiding and dries to a uniform elegant flat finish.

RECOMMENDED USES

- Masonry block
- Wallboard
- Primed wood
- Primed metal
- Previously painted surfaces
- Plaster

LIMITATIONS

- Do not apply when air and surface temperature are below 50°F.

Finish	Flat
Vehicle Type	Vinyl Acrylic Resin
Pigment Type	Titanium Dioxide
Solvent Type	Water
Coating Category	VOC 50 g/l max
% Solid by Weight	56% +/- 2%
% Solid by Volume	30% +/- 2%
Weight/Per Gallon	12 lbs / gal minimum
Recommended Dry Film by Coat	1.3 to 1.7 mils per coat
Theoretical Coverage	350-450 sq ft. / gallon
Dry Time Average	To touch: 1 hour To recoat: 4 hours
Application Method	Brush, roller, spray
Shelf Life	2 Years
Packaged	One, two and five gallon pails
Flash Point	Over 200°F (93°C)
Colors	Standard & custom colors
Federal Specification	TT-P-29J

SURFACE PREPARATION

All substrates must be dry and surfaces clean, free of dust, grease, oil, mortar spatter, form oils and any other contaminants. Level mortar projections by grinding or scraping, New masonry must cure a minimum of 30 days.

APPLICATION CONDITIONS

Apply when air and surface temperature is between 50°F and 90°F. Relative humidity 85% maximum.

APPLICATION EQUIPMENT

Brush –Use finest quality synthetic fiber/ bristle.
 Roller –1/4-3/8 nap- smooth surface.
 3/4-1/4 nap- rough surface.
 Spray – Fluid pressure-80-100 PSI
 Tip- 0.15-0.19 orifice

THINNING / CLEAN UP INSTRUCTIONS

If thinning is necessary add no more than 1/2 pint of clean water per gallon. Clean all equipment with warm soapy water. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

ENVIRONMENTAL INFORMATION

Meets or exceeds the criteria set forth by the U.S. Green buildings council LEED-CI, version 2.0 and LEED-NC, version 2.2. Contains no lead, mercury or chromate hazardous compounds. Complies with NY, NJ, and other states' requirements for limitation of volatile organic compounds. Meets New York Part 205 architectural surface coatings. Meets criteria for non-photochemical solvents in accordance with New York City Law 49.

Keep out of reach of children.
Protect from freezing.
Material Safety Data Sheets available upon request.

HEALTH & SAFETY INFORMATION

Do not take internally. Use only with adequate ventilation. Avoid contact with skin and breathing of vapors or spray mist. Wear eye protection and gloves during application.

ACCURACY OF DATA

The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit www.mercurypaint.com for the newest version of this data sheet.

RECOMMENDED SYSTEMS

Plaster / Drywall New	Primer: Series 5300 Finish: Series 6000 Interior Latex Flat
Plaster / Drywall Repainted	Primer: Series 5300 Finish: Series 6000 Interior Latex Flat
Wood New	Primer: Series 5300 Finish: Series 6000 Interior Latex Flat
Wood Repainted	Primer: Series 5300 Finish: Series 6000 Interior Latex Flat
Masonry	Primer: Series 5300 Finish: Series 6000 Interior Latex Flat
Masonry Repainted	Primer: Series 5300 Finish: Series 6000 Interior Latex Flat
Ferrous Metal New	Primer: Series 3000 Metal Primer Finish: Series 6000 Inter Latex Flat
Ferrous Metal Repainted	Primer: Series 3000 Metal Primer Finish: Series 6000 Inter Latex Flat

WARRANTY

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor of other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.

