

# SERIES 9900/9901

## ACRYLIC LATEX TRAFFIC PAINT



### PRODUCT FEATURES

- Quick dry
- Tough finish
- Weather resistant
- Abrasion resistant
- High visibility
- Excellent hiding

### GENERAL PROPERTIES

A fast dry interior/ exterior high visibility, heavy-duty traffic paint.

### RECOMMENDED USES

- Concrete
- Asphalt
- Curbs
- Parking lots
- Traffic aisles
- Storage areas

### LIMITATIONS

- Do not apply when air and surface temperature are below 50°F.

<b>Finish</b>	Flat
<b>Vehicle Type</b>	100% Acrylic
<b>Pigment Type</b>	Durable pigment, lead & chromate free
<b>Solvent Type</b>	Water
<b>Coating Category</b>	Traffic Marking Coating VOC 150 g/l max
<b>% Solid by Weight</b>	60% minimum
<b>% Solid by Volume</b>	40% minimum
<b>Weight/Per Gallon</b>	13 lbs / gal minimum
<b>Recommended Dry Film by Coat</b>	6.50-7.50 mils
<b>Theoretical Coverage</b>	300-345 lined ft/ gal @ 4 inches
<b>Viscosity @ 77° F</b>	80-95 KU
<b>Dry Time Average</b>	8 minutes @ 70°F
<b>Application Method</b>	Brush, roller, spray
<b>Shelf Life</b>	2 Years
<b>Packaged</b>	One and five gallon pails
<b>Flash Point</b>	N/A
<b>Colors</b>	Yellow, white, handicap blue & custom colors
<b>Federal Specification</b>	TT-P-1952 D



### **SURFACE PREPARATION**

All surfaces must be clean of dirt, grease, wax, foreign matter, peeling or chalky paint. Oil and grease have to be degreased.

### **APPLICATION CONDITIONS**

Do not apply over moisture or wet surfaces.  
Air and surface temperature must be above 50°F.

### **APPLICATION EQUIPMENT**

Brush – Any good quality  
Roller- Any good quality  
Spray- Use stripping equipment

### **THINNING / CLEAN UP INSTRUCTIONS**

Do not thin.

### **ENVIRONMENTAL INFORMATION**

Contains no lead, mercury or chromate hazardous compounds. Complies with N.Y., N.J. and other states' requirements for limitation of volatile organic compounds. Meets New York Part 205 architectural surface coatings. Meets criteria for non-photochemical solvents in accordance with New York City Law 49.

**Keep out of reach of children.**

**Safety Data Sheets available upon request.**

**Protect from freezing.**

### **HEALTH & SAFETY INFORMATION**

Use only with adequate ventilation. Do not breathe vapors, spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves.

### **RECOMMENDED SYSTEMS**

<b>Concrete</b>	Finish: Series 9900/9901
<b>Asphalt</b>	Finish: Series 9900/9901

### **ACCURACY OF DATA**

The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit [www.mercurypaint.com](http://www.mercurypaint.com) for the newest version of this data sheet.

### **WARRANTY**

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor of other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.

