

# SERIES 6000

## ACRYLIC LATEX FLAT FINISH



### PRODUCT FEATURES

- Hi-hiding
- Washable
- Low odor
- Self priming
- Soap & water clean up
- Fire retardant ASTM E-84
- Meets LEED-CI, version 2.0
- Meets LEED-NC, version 2.2
- EPA test method 24 VOC <50 g/l

### GENERAL PROPERTIES

A quality acrylic latex paint that is easy to apply, has excellent hiding and dries to a uniform elegant flat finish.

### RECOMMENDED USES

- Masonry block
- Wallboard
- Primed wood
- Primed metal
- Previously painted surfaces
- Plaster

### LIMITATIONS

- Do not apply when air and surface temperature are below 50°F.

<b>Finish</b>	Flat
<b>Vehicle Type</b>	Vinyl Acrylic Resin
<b>Pigment Type</b>	Titanium Dioxide
<b>Solvent Type</b>	Water
<b>Coating Category</b>	<50 g/l
<b>% Solid by Weight</b>	56% +/- 2%
<b>% Solid by Volume</b>	30% +/- 2%
<b>Weight/Per Gallon</b>	12 lbs / gal minimum
<b>Recommended Dry Film by Coat</b>	1.3 to 1.7 mils per coat
<b>Theoretical Coverage</b>	350-450 sq ft. / gallon
<b>Dry Time Average</b>	To touch: 1 hour To recoat: 4 hours
<b>Application Method</b>	Brush, roller, spray
<b>Shelf Life</b>	2 Years
<b>Packaged</b>	One, two and five gallon pails
<b>Flash Point</b>	Over 200°F (93°C)
<b>Colors</b>	Standard & custom colors
<b>Federal Specification</b>	TT-P-29J



**SURFACE PREPARATION**

All substrates must be dry and surfaces clean, free of dust, grease, oil, mortar spatter, form oils and any other contaminants. Level mortar projections by grinding or scraping, New masonry must cure a minimum of 30 days.

**APPLICATION CONDITIONS**

Apply when air and surface temperature is between 50°F and 90°F. Relative humidity 85% maximum.

**APPLICATION EQUIPMENT**

Brush –Use finest quality synthetic fiber/ bristle.  
 Roller –1/4-3/8 nap- smooth surface.  
           3/4-1/4 nap- rough surface.  
 Spray – Fluid pressure-80-100 PSI  
           Tip- 0.15-0.19 orifice

**THINNING / CLEAN UP INSTRUCTIONS**

If thinning is necessary add no more than 1/2 pint of clean water per gallon. Clean all equipment with warm soapy water. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

**ENVIRONMENTAL INFORMATION**

Meets or exceeds the criteria set forth by the U.S. Green buildings council LEED-CI, version 2.0 and LEED-NC, version 2.2. Contains no lead, mercury or chromate hazardous compounds. Complies with NY, NJ, and other states' requirements for limitation of volatile organic compounds. Meets New York Part 205 architectural surface coatings. Meets criteria for non-photochemical solvents in accordance with New York City Law 49.

Keep out of reach of children.

Protect from freezing.

Material Safety Data Sheets available upon request.

**HEALTH & SAFETY INFORMATION**

Do not take internally. Use only with adequate ventilation. Avoid contact with skin and breathing of vapors or spray mist. Wear eye protection and gloves during application.

**ACCURACY OF DATA**

The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit [www.mercurypaint.com](http://www.mercurypaint.com) for the newest version of this data sheet.

**RECOMMENDED SYSTEMS**

<b>Plaster / Drywall New</b>	Primer: Series 5300 Finish: Series 6000 Interior Latex Flat
<b>Plaster / Drywall Repainted</b>	Primer: Series 5300 Finish: Series 6000 Interior Latex Flat
<b>Wood New</b>	Primer: Series 5300 Finish: Series 6000 Interior Latex Flat
<b>Wood Repainted</b>	Primer: Series 5300 Finish: Series 6000 Interior Latex Flat
<b>Masonry</b>	Primer: Series 5300 Finish: Series 6000 Interior Latex Flat
<b>Masonry Repainted</b>	Primer: Series 5300 Finish: Series 6000 Interior Latex Flat
<b>Ferrous Metal New</b>	Primer: Series 3000 Metal Primer Finish: Series 6000 Inter Latex Flat
<b>Ferrous Metal Repainted</b>	Primer: Series 3000 Metal Primer Finish: Series 6000 Inter Latex Flat

**WARRANTY**

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor of other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.

