



Mercury Paint

Issuing Date No data available

# SAFETY DATA SHEET

Revision Date 10-Jun-2015



Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

Product Name SERIES 5300 LATEX PRIMER WHITE- PASTEL

### Other means of identification

Synonyms None

### Recommended use of the chemical and restrictions on use

Recommended Use Paint, Latex

Uses advised against No information available

### Details of the supplier of the safety data sheet

Supplier Name MERCURY PAINT

Supplier Address 4808 FARRAGUT ROAD  
BROOKLYN  
NY  
11203  
US

Supplier Phone Number Phone:7184698787  
Fax:7184698787

Supplier Email VGANDHI@MERCURYPAINT.COM

### Emergency telephone number

Company Emergency Phone Number CHEMTREC18004249300

## 2. HAZARDS IDENTIFICATION

### Classification




This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 2

### GHS Label elements, including precautionary statements

#### Emergency Overview

<b>Signal word</b>	<b>Danger</b>		
<b>Hazard Statements</b>			
Causes serious eye irritation			
May cause genetic defects			
Suspected of causing cancer			
			
<b>Appearance</b>	White to off-white	<b>Physical state</b>	Liquid
		<b>Odor</b>	No data available

#### Precautionary Statements - Prevention

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Wear eye/face protection

#### Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention

#### Precautionary Statements - Storage

Store locked up

#### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

#### Unknown Toxicity

35.0362% of the mixture consists of ingredient(s) of unknown toxicity

#### Other information

No information available

#### Interactions with Other Chemicals

No information available.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Limestone	1317-65-3	10 - 30	*
Titanium dioxide	13463-67-7	5 - 10	*
Kaolin	1332-58-7	5 - 10	*
Vinyl acetate	108-05-4	5 - 10	*
Hydrous Alum Silicates	1332-58-7	1 - 5	*
Propylene Glycol	57-55-6	1 - 5	*
Polyethylene glycol branched nonylphenyl ether	68412-54-4	0.1 - 1	*
Mineral Spirits (Rule 66)	8052-41-3	0.1 - 1	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret

### 4. FIRST AID MEASURES

#### First aid measures

<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	Wash with soap and water.
<b>Inhalation</b>	Remove to fresh air.
<b>Ingestion</b>	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

#### Most important symptoms and effects, both acute and delayed

**Most Important Symptoms and Effects** Burning sensation.

#### Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

### Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

No information available.

#### **Uniform Fire Code**

Irritant: Liquid  
Combustible Liquid: III-B

### Hazardous Combustion Products

Carbon oxides. Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

### Explosion Data

**Sensitivity to Mechanical Impact** No.

**Sensitivity to Static Discharge** No.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

**Other Information** Refer to protective measures listed in Sections 7 and 8.

### Environmental precautions

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8.

### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers. Soak up with inert absorbent material.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

**Incompatible Products** Acid chlorides. Acid anhydrides. Chloroformates. Strong oxidizing agents. Strong reducing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Limestone 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> (vacated) TWA: 15 mg/m <sup>3</sup> (vacated) TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> respirable dust TWA: 10 mg/m <sup>3</sup> total dust
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
Kaolin 1332-58-7	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Vinyl acetate 108-05-4	STEL: 15 ppm TWA: 10 ppm	(vacated) TWA: 10 ppm (vacated) TWA: 30 mg/m <sup>3</sup> (vacated) STEL: 20 ppm (vacated) STEL: 60 mg/m <sup>3</sup>	Ceiling: 4 ppm 15 min Ceiling: 15 mg/m <sup>3</sup> 15 min
Hydrous Alum Silicates 1332-58-7	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Mineral Spirits (Rule 66) 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m <sup>3</sup>	IDLH: 20000 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

### Appropriate engineering controls



**Engineering Measures**  
 Showers  
 Eyewash stations  
 Ventilation systems

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** If splashes are likely to occur: Wear safety glasses with side shields (or goggles). None required for consumer use.

**Skin and body protection** Wear protective gloves and protective clothing.

**Respiratory protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Physical and Chemical Properties**

<b>Physical state</b>	Liquid	<b>Odor</b>	No data available
<b>Appearance</b>	White to colors	<b>Odor Threshold</b>	No information available
<b>Color</b>	No information available		

<b><u>Property</u></b>	<b><u>Values</u></b>	<b><u>Remarks</u></b>	<b><u>Method</u></b>
<b>pH</b>	8+	None known	
<b>Melting / freezing point</b>	No data available	None known	
<b>Boiling point / boiling range</b>	>37.78 C (>100 F)	None known	
<b>Flash Point</b>	>94 C / >201 F	None known	
<b>Evaporation Rate</b>	No data available	None known	
<b>Flammability (solid, gas)</b>	No data available	None known	
<b>Flammability Limit in Air</b>			
<b>Upper flammability limit</b>	No data available		
<b>Lower flammability limit</b>	No data available		
<b>Vapor pressure</b>	No data available	None known	
<b>Vapor density</b>	No data available	None known	
<b>Specific Gravity</b>	1.404	None known	
<b>Water Solubility</b>	Soluble in water	None known	
<b>Solubility in other solvents</b>	No data available	None known	
<b>Partition coefficient: n-octanol/water</b>	No data available	None known	
<b>Autoignition temperature</b>	No data available	None known	
<b>Decomposition temperature</b>	No data available	None known	
<b>Kinematic viscosity</b>	No data available	None known	
<b>Dynamic viscosity</b>	No data available	None known	
<b>Explosive properties</b>	No data available		
<b>Oxidizing properties</b>	No data available		

**Other Information**

<b>Softening Point</b>	No data available
<b>VOC Content (%)</b>	66.84% (V/V), 47.54% (V/w)
<b>Particle Size</b>	No data available

**Particle Size Distribution****10. STABILITY AND REACTIVITY****Reactivity**

No data available.

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Hazardous Polymerization**

Hazardous polymerization does not occur.

**Conditions to avoid**

None known based on information supplied.

**Incompatible materials**

Acid chlorides. Acid anhydrides. Chloroformates. Strong oxidizing agents. Strong reducing agents.

**Hazardous Decomposition Products**

Carbon oxides. Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure****Product Information**

<b>Inhalation</b>	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
Vinyl acetate 108-05-4	= 2920 mg/kg ( Rat )	= 2320 mg/kg ( Rabbit )	= 11400 mg/m <sup>3</sup> ( Rat ) 4 h = 11.4 mg/L ( Rat ) 4 h
Propylene Glycol 57-55-6	= 20000 mg/kg ( Rat )	= 20800 mg/kg ( Rabbit )	-
Polyethylene glycol branched nonylphenyl ether 68412-54-4	-	= 1780 µL/kg ( Rabbit )	-

**Information on toxicological effects**

**Symptoms** May cause redness and tearing of the eyes.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**Mutagenic Effects** There is no data available for this product. Contains a known or suspected mutagen.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7		Group 2B		X
Vinyl acetate 108-05-4	A3	Group 2B		X

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 2B - Possibly Carcinogenic to Humans

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

**Reproductive toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Chronic Toxicity**

No known effect based on information supplied. Contains a known or suspected mutagen. Possible risk of irreversible effects. Contains a known or suspected carcinogen. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.

**Target Organ Effects**

Eyes. May affect the genetic material in germ cells (sperm and eggs). Respiratory system. Skin. Gastrointestinal tract (GI). Lungs.

**Aspiration Hazard** No information available.

**Numerical measures of toxicity Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)**

16,972.00 mg/kg

**ATEmix (dermal)**

17,466.00 mg/kg (ATE)

**ATEmix (inhalation-gas)**

34,539.00 ppm (4 hr)

**ATEmix (inhalation-dust/mist)**

11.51 mg/l

**ATEmix (inhalation-vapor)**

84.00 ATEmix



## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Vinyl acetate 108-05-4		96h LC50: = 14 mg/L (Pimephales promelas) 96h LC50: 15.04 - 21.54 mg/L (Lepomis macrochirus) 96h LC50: 26.1 - 36.63 mg/L (Poecilia reticulata)	EC50 = 2080 mg/L 5 min	24h EC50: = 52 mg/L
Propylene Glycol 57-55-6	96h EC50: = 19000 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 51600 mg/L (Oncorhynchus mykiss) 96h LC50: 41 - 47 mL/L (Oncorhynchus mykiss) 96h LC50: = 51400 mg/L (Pimephales promelas) 96h LC50: = 710 mg/L (Pimephales promelas)	-	24h EC50: > 10000 mg/L 48h EC50: > 1000 mg/L

### Persistence and Degradability

No information available.

### Bioaccumulation

Chemical Name	Log Pow
Vinyl acetate 108-05-4	0.73

### Other adverse effects

No information available.

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

#### Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

#### California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Vinyl acetate 108-05-4	Toxic Ignitable



## 14. TRANSPORT INFORMATION

<u>DOT</u> Proper Shipping Name Hazard Class	NOT REGULATED NON REGULATED N/A
<u>TDG</u>	Not regulated
<u>MEX</u>	Not regulated
<u>ICAO</u>	Not regulated
<u>IATA</u> Proper Shipping Name Hazard Class	Not regulated NON REGULATED N/A
<u>IMDG/IMO</u> Hazard Class	Not regulated N/A
<u>RID</u>	Not regulated
<u>ADR</u>	Not regulated
<u>ADN</u>	Not regulated

## 15. REGULATORY INFORMATION

### International Inventories

TSCA DSL	Complies All components are listed either on the DSL or NDSL.
-------------	--

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

### US Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Vinyl acetate - 108-05-4	108-05-4	5 - 10	0.1

#### SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)



Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Vinyl acetate 108-05-4	5000 lb			X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Vinyl acetate 108-05-4	5000 lb	5000 lb	RQ 5000 lb final RQ RQ 2270 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Formaldehyde - 50-00-0	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Limestone 1317-65-3	X	X	X		
Kaolin 1332-58-7	X	X	X		
Titanium dioxide 13463-67-7	X	X	X		
Vinyl acetate 108-05-4	X	X	X	X	X
Hydrous Alum Silicates 1332-58-7	X	X	X		
Propylene Glycol 57-55-6	X		X		

**International Regulations**

**Mexico**

**National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Limestone 1317-65-3 ( 10 - 30 )		Mexico: TWA= 10 mg/m <sup>3</sup> Mexico: STEL= 20 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7 ( 5 - 10 )		Mexico: TWA= 10 mg/m <sup>3</sup> Mexico: STEL= 20 mg/m <sup>3</sup>
Kaolin 1332-58-7 ( 5 - 10 )		Mexico: TWA= 10 mg/m <sup>3</sup> Mexico: STEL= 20 mg/m <sup>3</sup>
Vinyl acetate 108-05-4 ( 5 - 10 )	A3	Mexico: TWA 10 ppm Mexico: TWA 30 mg/m <sup>3</sup> Mexico: STEL 20 ppm Mexico: STEL 60 mg/m <sup>3</sup>
Hydrous Alum Silicates 1332-58-7 ( 1 - 5 )		Mexico: TWA 10 mg/m <sup>3</sup> Mexico: STEL 20 mg/m <sup>3</sup>
Mineral Spirits (Rule 66) 8052-41-3 ( 0.1 - 1 )		Mexico: TWA 100 ppm Mexico: TWA 523 mg/m <sup>3</sup> Mexico: STEL 200 ppm Mexico: STEL 1050 mg/m <sup>3</sup>

Mexico - Occupational Exposure Limits - Carcinogens  
A3 - Confirmed Animal Carcinogen



Canada  
**WHMIS Hazard Class**  
 Not determined

## 16. OTHER INFORMATION

<b>NFPA</b>	<b>Health Hazards</b> 2	<b>Flammability</b> 1	<b>Instability</b> 0	<b>Physical and Chemical Hazards</b> -
<b>HMIS</b>	<b>Health Hazards</b> 2 *	<b>Flammability</b> 1	<b>Physical Hazard</b> 0	<b>Personal Protection</b> X

**Chronic Hazard Star Legend** \* = Chronic Health Hazard

<b>Prepared By</b>	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501
<b>Revision Date</b>	10-Jun-2015
<b>Revision Note</b>	No information available

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**

