

SERIES 6900

EVERFRESH LATEX FLAT FINISH ZERO VOC



PRODUCT FEATURES

- Zero VOC
- Low odor
- Durable
- Hi-Hiding
- Quick return to service
- Meets LEED-NC, version 2.2
- Meets LEED-CI, version 2.0
- EPA test method 24 VOC <50 g/l
- Washable

GENERAL PROPERTIES

A low odor, zero VOC flat finish. This hi-hiding durable finish meets LEED-CI version 2.0 and LEED NC-version 2.2. An excellent coating that helps facilitate quick return to service.

RECOMMENDED USES

- Walls & ceilings
- Sheetrock
- Plaster
- Masonry
- Primed wood & metal
- Residential & schools
- Hospitals & institutions
- Facility management

LIMITATIONS

- Do not apply when air and surface temperature are below 50°F.
- Tinting may increase the VOC.

Finish	Flat
Vehicle Type	100% Acrylic
Pigment Type	Titanium Dioxide
Solvent Type	Water
Coating Category	Zero
% Solid by Weight	56% minimum
% Solid by Volume	37% minimum
Weight/Per Gallon	11.45 lbs/gal minimum
Recommended Dry Film by Coat	1.5 to 2 mils per coat
Theoretical Coverage	400-500 sq ft. / gallon
Viscosity @ 77° F	90-100 KU minimum
Dry Time Average	To touch: 30 min To recoat: 1 hour
Application Method	Brush, roller, spray
Shelf Life	2 Years
Packaged	One, two and five gallon pails
Flash Point	N/A
Colors	White and custom colors upon request
Federal Specification	Proprietary



SURFACE PREPARATION

All surfaces must be dry, thoroughly clean, free of loose paint, rust, grease, oil and all other foreign matter.

APPLICATION CONDITIONS

Do not apply over moisture or wet surfaces.
Air and surface temperature must be above 50°F.

APPLICATION EQUIPMENT

Brush – Use finest quality nylon or bristle brush.
Roller – 1/4-3/8 nap- smooth surface
 3/4-1 1/4 nap- rough surface
Spray – Fluid pressure 1,500-2,000 PSI
 Tip- 0.18 orifice

THINNING / CLEAN UP INSTRUCTIONS

Do not thin. Use as supplied. Do not add paint or solvent.

ENVIRONMENTAL INFORMATION

Contains no lead, mercury or chromate hazardous compounds. Complies with N.Y., N.J. and other states' requirements for limitation of volatile organic compounds. Meets New York Part 205 architectural surface coatings. Meets criteria for non-photochemical solvents in accordance with New York City Law 49.

Keep out of reach of children.
Safety Data Sheets available upon request.
Keep from freezing.

HEALTH & SAFETY INFORMATION

Use only with adequate ventilation. When ventilation is inadequate use respirator. Avoid contact with skin and breathing of vapors or spray mist. In case of eye contact, flush immediately with water.

RECOMMENDED SYSTEMS

Plaster/ Drywall New & Repainted	Primer: Series 5900 Everfresh Finish: Series 6900 Flat
Wood New/ Repainted	Primer: Series 5900 Everfresh Finish: Series 6900 Flat
Masonry New/ Repainted	Primer: Series 5900 Everfresh Finish: Series 6900 Flat
Ferrous Metal New/ Repainted	Primer: Series 3000 Metal Primer Finish: Series 6900 Flat
Galvanized Metal New/ Repainted	Primer: Series 2100 Latex Metal Primer Finish: Series 6900 Flat

ACCURACY OF DATA

The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit www.mercurypaint.com for the newest version of this data sheet.

WARRANTY

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor of other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.

