



Mercury Paint SERIES 5501 SWIMMING POOL PAINT SPLASH GUARD

PRODUCT FEATURES

- Protects against UV
- Protects against chlorine
- Durable / Fast Drying
- Resists fade
- Resists Chemicals
- Resists abrasion
- Self priming

GENERAL PROPERTIES

A premium water chlorinated rubber coating that is easy to apply and clean up. This self priming pool paint will provide long lasting protection against fading. Can be applied on damp surfaces.

RECOMMENDED USES

- Concrete surfaces
- Plaster surfaces
- Gunitite pools
- Fountains
- Fresh and Salt water pools
- Pool decks

LIMITATIONS

- Do not apply when air and surface temperature are below 50°F
- Do not use on fiberglass
- Do not use on Spas or Hot Tubs
- Wait 5-7 days before filling pool

TECHNICAL DATA

Finish	Semi Gloss
Vehicle Type	Chlorinated Rubber
Pigment Type	TiO ₂
Solvent Type	Aromatic Solvent - Xylene
VOC limit	340 grams per liter maximum
% Solid by Weight	52% minimum
% Solid by Volume	36%_minimum
Weight/Per Gallon	9.10 lb/per gal ± .05
Recommended Dry Film by Coat	6 mil
Theoretical Coverage	250 sq/ft per gallon @ 2 mils
Viscosity @ 77° F	75-90 KU
Dry Time Average	Dries 30 minutes - Recoat 24 hours
Application Method	Brush, Roller or Spray
Shelf Life	One year
Packaged	One and Five gallon pails
Flash Point	N/A
Colors	White, Pool Blue, Black, Red, Aqua and Sky Blue
Federal Specification	Proprietary



Mercury Paint

SURFACE PREPARATION

Water blast the surface to remove all loose paint, oils and grease. Decks must be cleaned with TSP wash, scrubbing surface to get rid of oil, dirt and suntan lotions, and then etched with a 15-20% solution of muratic acid. Then thoroughly rinse with TSP & flush with plenty of fresh water & and allowed to dry thoroughly. Glossy surfaces should be power sanded to a 80 grit profile for proper adhesion. **WAIT 7 DAYS AFTER FINAL COAT BEFORE FILLING POOL WITH WATER.**

HEALTH & SAFETY INFORMATION

CONTAINS XYLENE

See Material Safety Data Sheet for this product.

Keep away from heat, sparks and flame. Avoid breathing of vapor spray or spray mist. Avoid contact with the skin. Keep closures tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations. Do not take internally.

KEEP OUT OF REACH OF CHILDREN.

Use with adequate ventilation during application and drying. In tanks and other confined areas, use only with adequate forced air ventilation to prevent dangerous concentrations of vapors which could cause death from explosion or breathing. Use fresh air masks, clean protective clothing and explosion-proof equipment. Prevent flames, sparks, welding and smoking. Follow OSHA regulations regarding ventilation and respiratory equipment.

Keep out of reach of children.

Protect from freezing.

Material Safety Data Sheets available upon request.

APPLICATION EQUIPMENT

Brush - Use finest quality nylon or bristle brush.

Roller - 1/4-3/8 nap - smooth surface

3/4 - 1 1/4 nap -rough surface

Spray - Standard airless equipment such as the Graco President or Bulldog 30:1 pump ratio. Inbound pressure 80-100 psi, .013"-.017".

FIRST AID

If swallowed, do not induce vomiting. Call physician immediately. In case of eye contact, hold eye lids open and immediately flush with plenty of lukewarm water for at least 15 minutes. Get medical attention. In case of skin contact, wash thoroughly with soap and water. If irritation persists, seek medical attention. **USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.** Reports have associated repeated and prolonged exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. In case of fire use dry chemical, foam, water for or CO₂, cool closed containers with water. Photochemically Reactive.

ACCURACY OF DATA

The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit www.mercurypaint.com for the newest version of this data sheet.

WARRANTY

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor of other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.

Mercury Paint