

SAFETY DATA SHEET



Issuing Date No data available

Revision Date 10-Jun-2015

Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name

SERIES 8900 EVERFRESH ZERO VOC SEMI GLOSS FINISH

Other means of identification

Synonyms

None

Recommended use of the chemical and restrictions on use

Recommended Use

Paint, Latex

Uses advised against

No information available

Details of the supplier of the safety data sheet

Supplier Name

MERCURY PAINT

Supplier Address

4808 FARRAGUT ROAD

BROOKLYN

NY 11203 US

Supplier Phone Number

Phone:7184698787

Fax:7184698787

Supplier Email

VGANDHI@MERCURYPAINT.COM

Emergency telephone number

Company Emergency Phone

Number

CHEMTREC18004249300

2. HAZARDS IDENTIFICATION

Classification



This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 2

GHS Label elements, including precautionary statements

Emergency Overview

Signal word

Danger

Hazard Statements

Causes serious eye irritation May cause genetic defects Suspected of causing cancer



Appearance White to off-white

Physical state Liquid

Odor No data available

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Wear eye/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

Not applicable



Other information

No information available

Interactions with Other Chemicals

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Titanium dioxide	13463-67-7	10 - 25	*
Kaolin	1332-58-7	5 - 10	*
Vinyl acetate	108-05-4	40 - 50	*
			The state of the s
*Th =			

The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention

if irritation develops and persists.

Skin contact

Wash with soap and water.

Inhalation

Remove to fresh air.

Ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth

to an unconscious person. Do NOT induce vomiting. Call a physician.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Burning sensation.

Effects

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

No information available.

Uniform Fire Code

Irritant: Liquid

Combustible Liquid: III-B

Hazardous Combustion Products

Carbon oxides. Carbon monoxide. Carbon dioxide (CO₂).

Explosion Data

Sensitivity to Mechanical Impact

No.

Sensitivity to Static Discharge

No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Other Information

Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions

Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Pick up and transfer to properly labeled containers. Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off

contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Incompatible Products

Acid chlorides. Acid anhydrides. Chloroformates. Strong oxidizing agents. Strong reducing

agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

	ACGIH TLV	OSHA PEL	NIOSH IDLH
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³ total dust	IDLH: 5000 mg/m³
Kaolin 1332-58-7			TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust
Vinyl acetate 108-05-4	STEL: 15 ppm TWA: 10 ppm	(vacated) TWA: 10 ppm (vacated) TWA: 30 mg/m³ (vacated) STEL: 20 ppm (vacated) STEL: 60 mg/m³	Ceiling: 4 ppm 15 min Ceiling: 15 mg/m ³ 15 min
	13463-67-7 Kaolin 1332-58-7 Vinyl acetate	13463-67-7 Kaolin 1332-58-7 TWA: 2 mg/m³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction Vinyl acetate STEL: 15 ppm	TWA: 2 mg/m³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction (vacated) TWA: 10 mg/m³ total dust TWA: 15 mg/m³ respirable fraction (vacated) TWA: 10 mg/m³ total dust (vacated) TWA: 10 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction (vacated) TWA: 5 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction (vacated) TWA: 5 mg/m³ respirable fraction (vacated) TWA: 30 mg/m³ (vacated) TWA: 30 mg/m³ (vacated) STEL: 20 ppm

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures

Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

If splashes are likely to occur:. Wear safety glasses with side shields (or goggles). None

required for consumer use.



Skin and body protection

Wear protective gloves and protective clothing.

Respiratory protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state Appearance Color Liquid White to colors White

No data available

>37.78 C (>100 F)

>94 C / >201 F

No data available

Values

Odor Odor Threshold

Remarks Method

None known

None known

None known

None known

None known

No data available No information available

Property
pH
Melting / freezing point
Boiling point / boiling range
Flash Point
Evaporation Rate
Flammability (solid, gas)
Flammability Limit in Air
Upper flammability limit
Lower flammability limit

No data available No data available Lower flammability limit No data available Vapor pressure No data available Vapor density No data available Specific Gravity 1.29 Water Solubility Soluble in water Solubility in other solvents No data available Partition coefficient: n-octanol/waterNo data available Autoignition temperature No data available Decomposition temperature No data available Kinematic viscosity No data available Dynamic viscosity No data available **Explosive properties** No data available Oxidizing properties No data available None known

Other Information

Softening Point VOC Content (%) Particle Size No data available

Zero

No data available

Particle Size Distribution

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

None known based on information supplied.

Incompatible materials

Acid chlorides. Acid anhydrides. Chloroformates. Strong oxidizing agents. Strong reducing agents.

Hazardous Decomposition Products

Carbon oxides. Carbon monoxide. Carbon dioxide (CO2).

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye contact

Specific test data for the substance or mixture is not available. Causes serious eye

irritation. (based on components). May cause redness, itching, and pain.

Skin contact

Specific test data for the substance or mixture is not available. May cause irritation.

Prolonged contact may cause redness and irritation.

Ingestion

Specific test data for the substance or mixture is not available. Ingestion may cause

irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	_
Vinyl acetate 108-05-4	= 2920 mg/kg (Rat)	= 2320 mg/kg (Rabbit)	= 11400 mg/m³ (Rat) 4 h = 11.4 mg/L (Rat) 4 h
		,	

Information on toxicological effects

Symptoms

May cause redness and tearing of the eyes.

Delayed and immediate effects as well as chronic effects from short and long-term exposure



Sensitization

No information available.

Mutagenic Effects

There is no data available for this product. Contains a known or suspected mutagen.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7		Group 2B		×
Vinyl acetate 108-05-4	А3	Group 2B	A STATE OF THE PROPERTY OF THE	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity

No information available.

STOT - single exposure

No information available.

STOT - repeated exposure

No information available.

Chronic Toxicity

No known effect based on information supplied. Contains a known or suspected mutagen. Possible risk of irreversible effects. Contains a known or suspected carcinogen. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.

Target Organ Effects

Eyes. May affect the genetic material in germ cells (sperm and eggs). Respiratory system.

Skin. Gastrointestinal tract (GI). Lungs.

Aspiration Hazard

No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
16,972.00 mg/kg
ATEmix (dermal)
17,466.00 mg/kg (ATE)
ATEmix (inhalation-gas)
34,539.00 ppm (4 hr)
ATEmix (inhalation-dust/mist)
11.51 mg/l
ATEmix (inhalation-vapor)
84.00 ATEmix



12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Vinyl acetate 108-05-4		96h LC50: = 14 mg/L (Pimephales promelas) 96h LC50: 15.04 - 21.54 mg/L (Lepomis macrochirus) 96h LC50: 26.1 - 36.63 mg/L (Poecilia reticulata)	EC50 = 2080 mg/L 5 min	24h EC50: = 52 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow	
Vinyl acetate 108-05-4	0.73	

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Vinyl acetate	Toxic
108-05-4	Ignitable

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name

NOT REGULATED NON REGULATED



Hazard Class

N/A

TDG

Not regulated

MEX

Not regulated

ICAO

Not regulated

IATA

Not regulated

Proper Shipping Name

NON REGULATED

Hazard Class

N/A

IMDG/IMO

Not regulated

Hazard Class

N/A

RID

Not regulated

ADR

Not regulated

ADN

Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA

Complies

DSL

All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Vinyl acetate - 108-05-4	108-05-4	40 - 50	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Vinyl acetate 108-05-4	5000 lb			X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive



Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Vinyl acetate 108-05-4	5000 lb	5000 lb	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen

U.S. State Right-to-Know Regulations

Kaolin	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
13463-67-7 Vinyl acetate X X X X	X	×	X		THE RESERVE TO SERVE THE PARTY OF THE PARTY
	X	Χ.	X		
108-05-4	X	×	×	X	X
108-05-4		X X	New Jersey Massachusetts X X X X X X X	X X X	X X X

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Titanium dioxide		Mexico: TWA= 10 mg/m ³
13463-67-7 (10 - 25)		Mexico: STEL= 20 mg/m ³
Kaolin		Mexico: TWA= 10 mg/m ³
1332-58-7 (5 - 10)		Mexico: STEL= 20 mg/m ³
Vinyl acetate	A3	Mexico: TWA 10 ppm
108-05-4 (40 - 50)		Mexico: TWA 30 mg/m ³
		Mexico: STEL 20 ppm
		Mexico: STEL 60 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

A3 - Confirmed Animal Carcinogen

Canada

WHMIS Hazard Class

Not determined

46	OTHER	INICOL	ONAA"	TION
10.	OTHER	INFU	KIVIA	HON

NFPA

Health Hazards 1

Flammability 0

Instability 0

Physical and

HMIS

Health Hazards 1*

Flammability 0

Physical Hazard 0

Chemical Hazards -Personal Protection X

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By

Product Stewardship 23 British American Blvd.



Latham, NY 12110 1-800-572-6501

Revision Date Revision Note

10-Jun-2015 No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet