

SERIES 9/15

GLOSS ENAMEL



PRODUCT FEATURES

- 15 minutes to dry
- Durable
- Excellent gloss retention
- Excellent color retention
- Interior/Exterior
- Rust preventative

GENERAL PROPERTIES

Mercury gloss enamel series 9/15 is a premium quality architectural finish to be applied on all types of metal surfaces. Dries to tough washable gloss finish in 15 minutes. For professional and industrial use only.

RECOMMENDED USES

- Structural steel
- Metal
- Piping
- Doors
- Bucks
- Tanks
- Railings
- Metal cabinets
- Equipment
- Machinery

LIMITATIONS

- Do not apply when air and surface temperature are below 45°F
- For metal substrates only

Finish	Gloss
Vehicle Type	Alkyd
Pigment Type	Titanium Dioxide & Light Fast Pigments
Solvent Type	High flash naptha
Coating Category	Industrial Maintenance Coating VOC 250 g/l max
% Solid by Weight	60% minimum
% Solid by Volume	50% minimum
Weight/Per Gallon	8.00 lbs/ gal minimum
Recommended Dry Film by Coat	1.5 to 2.5 mils
Theoretical Coverage	450-500 sq ft. / gallon
Viscosity @ 77° F	65-95 KU
Dry Time Average	To touch: 10-15 minutes To recoat: 12 hrs
Application Method	Brush, roller, spray
Shelf Life	2 Years
Packaged	One, two, five gallon pails
Flash Point	105°F
Colors	Stock & custom colors upon request



SURFACE PREPARATION

All surfaces must be clean, dry, and free of dirt, grease, rust, chalk, loose and peeling paints.

APPLICATION CONDITIONS

Temperature: 45°F-100°F

Relative humidity: up to 85°F

Surface temperature: 5°F above dew point

APPLICATION EQUIPMENT

Brush – Good quality china bristle

Roller – Any high quality roller

Spray – Fluid pressure-2,000-2,500 PSI

Tip- 0.15-0.21 orifice

THINNING / CLEAN UP INSTRUCTIONS

Do not thin. Clean-up with xylene or mineral spirits.

ENVIRONMENTAL INFORMATION

Contains no lead, mercury or chromate hazardous compounds. Complies with NY and NJ and other states' requirements for limitation of volatile organic compounds.

Meets New York Part 205 architectural surface coatings.

Meets criteria for non-photochemical solvents in accordance with New York City Law 49.

Keep out of reach of children.

Protect from freezing.

Safety Data Sheets available upon request.

HEALTH & SAFETY INFORMATION

WARNING! FLAMMABLE. Contains mineral spirits and aromatic naphtha. Keep away from heat and open flame. Do not take internally. May irritate eyes and skin. Prolonged breathing of vapors may irritate respiratory tract causing headache, nausea and dizziness. Use only with adequate ventilation. Where ventilation is inadequate, use NIOSH/MSHA approved respirator. Avoid contact with skin and breathing or vapors or spray mist. Close container tightly and wash hands after each use.

ACCURACY OF DATA

The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit www.mercurypaint.com for the newest version of this data sheet.

WARRANTY

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor of other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.

