



# Mercury Paint **SERIES 99SSSS** **SPORTS SURFACE COATING**

|   |   |
|---|---|
| <p><b>PRODUCT FEATURES</b></p> <ul style="list-style-type: none"> <li>• Quick dry</li> <li>• Tough finish</li> <li>• Weather resistant</li> <li>• Abrasion resistant</li> <li>• High visibility</li> <li>• Excellent hiding</li> </ul> <p><b>GENERAL PROPERTIES</b></p> <p>A fast dry advanced technology for application over all types of sports courts.</p> <ul style="list-style-type: none"> <li>•Tennis courts</li> <li>•Basketball courts</li> <li>•Playground surfaces</li> </ul> | <p><b>RECOMMENDED USES</b></p> <ul style="list-style-type: none"> <li>• Concrete</li> <li>• Asphalt</li> <li>• Curbs</li> <li>• Parking lots</li> <li>• Sports Courts</li> <li>• Athletic Surfaces</li> </ul> <p><b>LIMITATIONS</b></p> <ul style="list-style-type: none"> <li>• Do not apply when air and surface temperature are below 50°F.</li> </ul> |
|---|---|

## TECHNICAL DATA

|                              |   |
|------------------------------|---|
| Finish                       | Flat  |
| Vehicle Type                 | 100% Acrylic                                    |
| Pigment Type                 | Durable pigment, lead & chromate free           |
| Solvent Type                 | Water   |
| Coating Category             | Flat VOC 50 g/l max                             |
| % Solid by Weight            | 50-60% minimum                                  |
| % Solid by Volume            | 40% minimum                                     |
| Weight/Per Gallon            | 11 lbs/gal minimum                              |
| Recommended Dry Film by Coat | 6.50 - 7.50 mils                                |
| Theoretical Coverage         | 200-300 sq ft per gal                           |
| Viscosity @ 77° F            | 80-95 KU Minimum                                |
| Dry Time Average             | 8 minutes @ 70°f                                |
| Application Method           | Brush, roller, spray                            |
| Shelf Life                   | 2 Years   |
| Packaged                     | One, and Five gallon Pails                      |
| Flash Point                  | N/A   |
| Colors                       | Green, Blue, Red, White, Yellow & custom colors |
|                              |   |



## Mercury Paint

**SURFACE PREPARATION**

All surfaces to be painted must be swept free of dust, dirt, or any loose ceiling paint left from previous coating. Oil and grease have to be degreased.

**APPLICATION CONDITIONING**

Do not apply over moisture or wet surfaces. Air and surface temperature must be above 50°F.

**APPLICATION EQUIPMENT**

Brush - Any good quality  
 Roller - Any good quality  
 Spray - Use stripping equipment

**THINNING / CLEAN UP INSTRUCTIONS**

Do not thin.

**RECOMMENDED SYSTEMS**

|          |                                 |
|----------|---------------------------------|
| Concrete | <b>Finish:</b> Series 9900/9901 |
| Asphalt  | <b>Finish:</b> Series 9900/9901 |

**ENVIRONMENTAL INFORMATION**

Contains no lead, mercury or chromate hazardous compounds. Complies with N.Y., N.J. and other states' requirements for limitation of volatile organic compounds. Meets New York Part 205 architectural surface coatings. Meets criteria for non-photochemical solvents in accordance with New York City Law 49.

**HEALTH & SAFETY INFORMATION**

**Use only with adequate ventilation.** Do not breathe vapors, spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves.

**Keep out of reach of children.**

**Protect from freezing.**

**Material Safety Data Sheets available upon request.**

|   |  |
|---|--|
| <p><b>ACCURACY OF DATA</b></p> <p>The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit <a href="http://www.mercurypaint.com">www.mercurypaint.com</a> for the newest version of this data sheet.</p> | <p><b>WARRANTY</b></p> <p>This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor or other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.</p> |
|---|--|

**Mercury Paint**