



# SAPOLIN PPX RTU ATHLETIC FIELD MARKING PAINT

## PRODUCT FEATURES

- Quick dry
- Weather resistant – Premium quality
- Custom colors upon request
- Soap & water clean-up
- For grass, synthetic turf & black top
- Ready to use formula (RTU)
- No thinning required

## GENERAL PROPERTIES

A heavy duty, exterior, vinyl-acrylic latex line marking paint. Dries within a ½ hour to a tough, durable weather resistant finish.

## RECOMMENDED USES

- Natural field turf
- Synthetic field turf
- Black top

## LIMITATIONS

- Do not apply at temperatures less than 45°F.

## TECHNICAL DATA

Finish	Flat
Vehicle Type	Vinyl-Acrylic
Pigment Type	Titanium Dioxide
Solvent Type	Water
Coating Category	Flat coating VOC < 50 g/l
% Solid by Weight	30% minimum
% Solid by Volume	15% minimum
Weight/Per Gallon	9.00 lbs/gal minimum
Recommended Dry Film by Coat	5-8 mils per coat
Theoretical Coverage	3 inch line – 575 lineal feet per gallon
Viscosity @ 75° F	70 KU minimum
Dry Time Average	15-20 minutes
Application Method	Stripping equipment
Shelf Life	2 Years
Packaged	Five gallon pails only
Flash Point	N/A
Colors	White, yellow, yale blue, red, orange, green and pink
Federal Specification	Proprietary

## Sapolin Paint Company

## SURFACE PREPARATION

All surfaces should be clean and dry.

## APPLICATION CONDITIONS

Minimum temperature 45°F.

## ENVIRONMENTAL INFORMATION

Meets or exceeds the criteria set forth by the U.S. Green buildings council LEED-CI, version 2.0 and LEED-NC version 2.2. Contains no lead, mercury or chromate hazardous compounds. Complies with N.Y., N.J. and other states' requirements for limitation of volatile organic compounds. Meets New York Part 205 architectural surface coatings. Meets criteria for non-photochemical solvents in accordance with New York City Law 49.

## APPLICATION EQUIPMENT

Spray – Stripping equipment

## THINNING / CLEAN UP INSTRUCTIONS

1 gallon of water to 1 gallon of Line Marking Paint.

## HEALTH & SAFETY INFORMATION

**Use only with adequate ventilation.** Do not breathe vapors, spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves.

**Keep out of reach of children.**

**Protect from freezing.**

**Material Safety Data Sheets available upon request.**

### ACCURACY OF DATA

The technical data presented above are true and accurate as of the date of issuance of this Sapolin Paint Company data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued.

### WARRANTY

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Sapolin Paint Company, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor or other consequential damages, provided that the purchaser notifies management of Sapolin Paint Company with twenty-four hours of the application of the product.

# Sapolin Paint Company