

ZOOM SERIES 6200

SURE GRIP ACRYLIC FLOOR FINISH



PRODUCT FEATURES

- Durable
- Chemical resistant
- Easy to apply
- Quick dry- 20 minutes
- Low odor
- Interior/Exterior
- Self priming

GENERAL PROPERTIES

A quick dry, water-based durable floor coating that is easy to apply. Excellent for residential and commercial applications. This coating has excellent durability that is comparable to latex epoxies. Also can be reduced with water to make a decorative concrete stain.

RECOMMENDED USES

- Driveways
- Concrete floors
- Basement floors
- Porches
- Patios
- Garages
- Light industrial application
- Concrete Pool Decks

LIMITATIONS

- Do not apply over bare wood.
- New concrete requires acid etching.
- Can be slippery. An anti-slip aggregate may be added.

Finish	Semi-Gloss
Vehicle Type	100% Acrylic
Pigment Type	Light Fast Pigments
Solvent Type	Water
Coating Category	Floor coating max VOC 100 g/l
% Solid by Weight	48% minimum
% Solid by Volume	36% minimum
Weight/Per Gallon	10.30 +/- .50 lbs/ gal
Recommended Dry Film by Coat	1.5 to 2.0 mils per coat
Theoretical Coverage	400-500 sq ft. / gallon
Viscosity @ 77° F	75 KU minimum
Dry Time Average	To touch: 20 min. To recoat: 2 hours.
Application Method	Brush, roller, spray
Shelf Life	2 Years
Packaged	One and Five gallon pails
Flash Point	N/A
Colors	10 stock colors and tinted colors upon request
Federal Specification	Proprietary



SURFACE PREPARATION

To insure adhesion and durability, prepare the surface properly. It must be clean and free of all wax, grease, oil, dirt, loose or flaking material, acid substance and soap deposits. To clean floor, scrub with detergent or solution of 1/2 cup trisodium phosphate per gallon of water; flush well with clean water. Glossy painted surfaces must be dulled. Smooth, hard-troweled concrete floors should be acid-etched before painting. Acid suitable for etching should be labeled with directions and precautions; observe them carefully.

APPLICATION CONDITIONS

Temperature: 50°F-110°F
Relative humidity: Up to 85% maximum

APPLICATION EQUIPMENT

Brush – Use finest quality nylon brush.
Roller – 1/2 nap- smooth surface
 1 1/4 nap- rough surface
Spray – Fluid pressure 1,500- 2,000 PSI
 Tip- .018 orifice.

THINNING / CLEAN UP INSTRUCTIONS

Can be thinned up to a 1/2 pint per gallon.

ENVIRONMENTAL INFORMATION

Contains no lead, mercury or chromate hazardous compounds. Complies with N.Y., N.J. and other states' requirements for limitation of volatile organic compounds.

Keep out of reach of children.

Protect from freezing.

Safety Data Sheets available upon request.

HEALTH & SAFETY INFORMATION

CAUSES EYE IRRITATION.

Use only with adequate ventilation. Do not breathe vapors, spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves during application or sanding. A dust/ particulate respirator approved by NIOSH should be worn when sanding or spraying. Close container after every use.

FIRST AID: If affected by inhalation of vapors or spray mist, remove to fresh air. In case of eye contact, flush immediately with plenty of water for at least 16 minutes and call a physician; for skin, wash thoroughly with soap and water. In case of ingestion, DO NOT INDUCE VOMITING. Get medical help immediately.

RECOMMENDED SYSTEMS

Concrete & Masonry	Primer: Series 6200 Finish: Sereies 6200
-------------------------------	---

ACCURACY OF DATA

The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit www.mercurypaint.com for the newest version of this data sheet.

WARRANTY

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor of other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.

