

# SERIES 5999

## EVERFRESH ZERO VOC CONVERSION PRIMER



### PRODUCT FEATURES

- Zero VOC
- Excellent adhesion
- Low odor
- Durable
- Hi- Hiding
- Quick return to service
- Meets LEED-NC, version 2.2
- Meets LEED-CI, version 2.0
- EPA test method 24- VOC <50 g/l

### GENERAL PROPERTIES

A low odor, zero VOC primer/ sealer for metal surfaces, galvanized metal and gloss surfaces. This coating meets LEED-NC, version 2.2 and LEED-CI, version 2.0. An excellent coating that helps facilitate quick return to service.

### RECOMMENDED USES

- Walls & ceilings
- Sheet rock
- Plaster & Masonry
- Metal substrate
- Glossy surfaces
- Galvanized metal
- Hospitals & institutions
- Senior citizen housing
- Facility management

### LIMITATIONS

- Do not apply when air and surface temperature are below 50°F.
- Tinting may increase the VOC.

<b>Finish</b>	Flat
<b>Vehicle Type</b>	Co-polymer
<b>Pigment Type</b>	Titanium Dioxide
<b>Solvent Type</b>	Water
<b>Coating Category</b>	Zero
<b>% Solid by Weight</b>	55% minimum
<b>% Solid by Volume</b>	35% minimum
<b>Weight/Per Gallon</b>	11.00 lbs / gal minimum
<b>Recommended Dry Film by Coat</b>	1.5 to 2.0 mils per coat
<b>Theoretical Coverage</b>	350-400 sq ft. / gallon
<b>Viscosity @ 77° F</b>	35 KU minimum
<b>Dry Time Average</b>	To touch: 30 min To recoat: 1 hour
<b>Application Method</b>	Brush, roller, spray
<b>Shelf Life</b>	2 Years
<b>Packaged</b>	One and five gallon pails
<b>Flash Point</b>	N/A
<b>Colors</b>	White and custom colors upon request
<b>Federal Specification</b>	Proprietary



**SURFACE PREPARATION**

All surfaces to be clean, dry and free of dirt, grease, rust, chalk, loose paint and any other foreign matter.

**APPLICATION CONDITIONS**

Do not apply over moisture or wet surfaces. Air and surface temperature must be above 50°F.

**APPLICATION EQUIPMENT**

Brush – Use finest quality nylon or bristle brush  
 Roller –1/4-3/8 nap- smooth surface  
           3/4- 1 1/4 nap- rough surface  
 Spray – Fluid pressure-1,500- 2,000 PSI  
           Tip- 0.18 orifice

**THINNING / CLEAN UP INSTRUCTIONS**

Do not thin. Use as supplied. Do not add paint or solvent.

**ENVIRONMENTAL INFORMATION**

Meets or exceeds the criteria set forth by the U.S. Green buildings council LEED-CI, version 2.0 and LEED-NC, version 2.2. Contains no lead, mercury or chromate hazardous compounds. Complies with N.Y., N.J. and other states' requirements for limitation of volatile organic compounds. Meets New York Part 205 architectural surface coatings. Meets criteria for non-photochemical solvents in accordance with New York City Law 49.

**Keep out of reach of children.**  
**Material Safety Data Sheets available upon request.**  
**Protect from freezing.**

**HEALTH & SAFETY INFORMATION**

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves. A dust/ particulate respirator approved by NIOSH should be worn when sanding or spraying. Close container after each use.

**RECOMMENDED SYSTEMS**

<b>Plaster/ Drywall New/ Repainted</b>	Primer: Series 5999 Everfresh Finish: Series 6900 (flat), Series 9150 (eggshell), Series 8900 (semi-gloss)
<b>Wood New/ Repainted</b>	Primer: Series 5999 Everfresh Finish: Series 6900 (flat), Series 9150 (eggshell), Series 8900 (semi-gloss)
<b>Masonry New/ Repainted</b>	Primer: Series 5999 Everfresh Finish: Series 6900 (flat), Series 9150 (eggshell), Series 8900 (semi-gloss)

**ACCURACY OF DATA**

The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit [www.mercurypaint.com](http://www.mercurypaint.com) for the newest version of this data sheet.

**WARRANTY**

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor of other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.

