

SERIES 5700

ACRYLIC LATEX HOUSE PAINT



PRODUCT FEATURES

- Easy to apply
- Excellent hiding
- Quick dry
- Mildew resistant
- Alkali resistant

GENERAL PROPERTIES

A heavy duty exterior 100% acrylic, low luster, mildew resistant coating which will withstand severe winter conditions. Covers graffiti in one coat.

RECOMMENDED USES

- Wood & aluminum siding
- Trim
- Shakes & shingles
- Cinder block
- Vinyl siding
- Concrete
- Stucco
- Brick
- Primed metal

LIMITATIONS

- Do not apply when air and surface temperature are below 50°F.

Finish	Low Luster
Vehicle Type	100% Acrylic
Pigment Type	Titanium Dioxide
Solvent Type	Water
Coating Category	Non-flat coating max VOC 100 g/l
% Solid by Weight	55% minimum
% Solid by Volume	36% minimum
Weight/Per Gallon	11.60 lbs / gal avg
Recommended Dry Film by Coat	1.5 to 2.0 mils per coat
Theoretical Coverage	350-410 sq ft. / gallon
Viscosity @ 77° F	85-95 KU
Dry Time Average	To touch: 1 hour To recoat: 3 hours
Application Method	Brush, roller, spray
Shelf Life	2 Years
Packaged	One, two and five gallon pails
Flash Point	N/A
Colors	White, standard and tinted colors upon request
Federal Specification	TT-P-1510A



SURFACE PREPARATION

All surfaces to be clean, dry and free of dirt, grease, rust, chalk, loose paint and any other foreign matter.

APPLICATION CONDITIONS

Temperature: 50°F-95°F
Relative humidity: up to 85%
Surface temperature: 5°F above dew point

APPLICATION EQUIPMENT

Brush – Good quality china bristle
Roller – Short nap roller
Spray – Fluid pressure-1,500- 3,000 PSI
Tip- 0.17- 0.19 orifice

THINNING / CLEAN UP INSTRUCTIONS

Thinning is not recommended. Use a small amount of water if needed. Clean brushes, rollers and equipment with warm water.

ENVIRONMENTAL INFORMATION

Contains no lead, mercury or chromate hazardous compounds. Complies with N.Y., N.J. and other states' requirements for limitation of volatile organic compounds. Meets New York Part 205 architectural surface coatings. Meets criteria for non-photochemical solvents in accordance with New York City Law 49.

Keep out of reach of children.
Material Safety Data Sheets available upon request.

HEALTH & SAFETY INFORMATION

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves during application or sanding. A dust/ particulate respirator approved by NIOSH should be worn when sanding or spraying. Close container after each use.

RECOMMENDED SYSTEMS

Wood New/ Repainted	Primer: Series 5600 Finish: Series 5700 Acrylic House Paint
Masonry New	Primer: Series 1000 Finish: Series 5700 Acrylic House Paint
Masonry Repainted	Primer: Series 2500 Finish: Series 5700 Acrylic House Paint
Steel New/ Repainted	Primer: Series 3000 Finish: Series 5700 Acrylic House Paint

ACCURACY OF DATA

The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit www.mercurypaint.com for the newest version of this data sheet.

WARRANTY

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor of other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.

