



Mercury Paint

Issuing Date No data available

# SAFETY DATA SHEET

Revision Date 10-Jun-2015



Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

Product Name MAT 9-15 RPC GLOSS ENAMEL WHITE-COLORS

### Other means of identification

Synonyms None

### Recommended use of the chemical and restrictions on use

Recommended Use Paint

Uses advised against No information available

### Details of the supplier of the safety data sheet

Supplier Name MERCURY PAINT

Supplier Address 4808 FARRAGUT ROAD  
BROOKLYN  
NY  
11203  
US

Supplier Phone Number Phone:7184698787  
Fax:7184698787

Supplier Email VGANDHI@MERCURYPAIN.COM

### Emergency telephone number

Company Emergency Phone Number CHEMTREC18004249300

## 2. HAZARDS IDENTIFICATION

### Classification




This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Aspiration toxicity	Category 1
Flammable liquids	Category 2

**GHS Label elements, including precautionary statements**

**Emergency Overview**

<b>Signal word</b>	<b>Danger</b>	
<b>Hazard Statements</b>	May cause an allergic skin reaction May cause genetic defects May cause cancer May be fatal if swallowed and enters airways Highly flammable liquid and vapor	
		
<b>Appearance</b>	Multiple Colors	<b>Physical state</b> Liquid
		<b>Odor</b> Solvent

**Precautionary Statements - Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Contaminated work clothing should not be allowed out of the workplace
- Wear protective gloves
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ ventilating/ lighting/ equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge

**Precautionary Statements - Response**

- IF exposed or concerned: Get medical advice/attention
- Specific treatment (see supplemental first aid instructions on this label)

**Skin**

- If skin irritation or rash occurs: Get medical advice/attention
- Wash contaminated clothing before reuse
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower



**Ingestion**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
Do NOT induce vomiting

**Fire**

In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Unknown Toxicity**

44.107% of the mixture consists of ingredient(s) of unknown toxicity

**Other information**

Harmful to aquatic life with long lasting effects  
Repeated or prolonged skin contact may cause allergic reactions with susceptible persons  
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

**Interactions with Other Chemicals**

Use of alcoholic beverages may enhance toxic effects.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Solvent naphtha (petroleum), light aliphatic	64742-89-8	10 - 30	*
Titanium dioxide	13463-67-7	10 - 30	*
Aromatic solvent	64742-95-6	7 - 13	*
Hydrous Alum Silicates	1332-58-7	5 - 10	*
Vinyl toluene	25013-15-4	1 - 5	*
Methyl ethyl ketoxime	96-29-7	0.1 - 1	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret

### 4. FIRST AID MEASURES

**First aid measures****General Advice**

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

**Eye contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing.



---

<b>Skin contact</b>	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
<b>Inhalation</b>	Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Seek immediate medical attention/advice. Delayed pulmonary edema may occur.
<b>Ingestion</b>	Aspiration hazard if swallowed - can enter lungs and cause damage. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.
<b>Self-protection of the first aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Remove all sources of ignition.

**Most important symptoms and effects, both acute and delayed**

<b>Most Important Symptoms and Effects</b>	Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.
--	--

**Indication of any immediate medical attention and special treatment needed**

<b>Notes to Physician</b>	May cause sensitization of susceptible persons. Treat symptomatically.
---------------------------	--

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray. Alcohol resistant foam.

### Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

Product is or contains a sensitizer. May cause sensitization by skin contact. Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

#### **Uniform Fire Code**

Sensitizer: Liquid  
Flammable Liquid: I-B

### Hazardous Combustion Products

Carbon oxides.

### Explosion Data

**Sensitivity to Mechanical Impact** No.

**Sensitivity to Static Discharge** Yes.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Evacuate personnel to safe areas. Ensure adequate ventilation. See section 8 for more information. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

**Other Information** Refer to protective measures listed in Sections 7 and 8. Ventilate the area.

### Environmental precautions

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways.

**Methods for cleaning up** Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Take off contaminated clothing and wash before reuse. Do not eat, drink or smoke when using this product. Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Protect from moisture. Store away from other materials. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

**Incompatible Products** None known based on information supplied.



## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
Hydrous Alum Silicates 1332-58-7	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Vinyl toluene 25013-15-4	STEL: 100 ppm TWA: 50 ppm	TWA: 100 ppm TWA: 480 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 480 mg/m <sup>3</sup>	IDLH: 400 ppm TWA: 100 ppm TWA: 480 mg/m <sup>3</sup>

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

### Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

### Appropriate engineering controls

### Engineering Measures

Showers  
Eyewash stations  
Ventilation systems

### Individual protection measures, such as personal protective equipment

### Eye/face protection

Tight sealing safety goggles.

### Skin and body protection

Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant apron. Impervious gloves. Antistatic boots.

### Respiratory protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

### Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Physical and Chemical Properties

Physical state  
Appearance  
Color

Liquid  
White & Multiple Colors  
No information available

Odor  
Odor Threshold

Solvent  
No information available



<u>Property</u>	<u>Values</u>	<u>Remarks</u> <u>Method</u>
pH	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	22 C / 72 F	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	1.137	None known
Water Solubility	Virtually insoluble	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing properties	No data available	

**Other Information**

Softening Point	No data available
VOC Content (%)	50.43% (V/V), 34.52% (V/w)
Particle Size	No data available
Particle Size Distribution	

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available.

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Hazardous Polymerization**

Hazardous polymerization does not occur.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

None known based on information supplied.

**Hazardous Decomposition Products**

Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure****Product Information**



<b>Inhalation</b>	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. May cause irritation.
<b>Skin contact</b>	Repeated exposure may cause skin dryness or cracking.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

### Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Solvent naphtha (petroleum), light aliphatic 64742-89-8	-	= 3000 mg/kg ( Rabbit )	-
Titanium dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
Aromatic solvent 64742-95-6	-	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h = 3400 ppm ( Rat ) 4 h
Methyl ethyl ketoxime 96-29-7	= 930 mg/kg ( Rat )	= 0.2 mg/kg ( Rabbit )	= 20 mg/L ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Asthma-like and/ or skin allergy-like symptoms.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** May cause sensitization of susceptible persons. May cause sensitization by skin contact.

**Mutagenic Effects** There is no data available for this product. Contains a known or suspected mutagen.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7		Group 2B		X
Vinyl toluene 25013-15-4		Group 3		

**IARC (International Agency for Research on Cancer)**

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

**Reproductive toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Chronic Toxicity** No known effect based on information supplied. Contains a known or suspected mutagen. Possible risk of irreversible effects. Contains a known or suspected carcinogen. Aspiration

may cause pulmonary edema and pneumonitis. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.

**Target Organ Effects**

Skin. May affect the genetic material in germ cells (sperm and eggs). Respiratory system. Eyes. Gastrointestinal tract (GI). Central Nervous System (CNS). Lungs. Kidney. Liver.

**Aspiration Hazard**

No information available.

**Numerical measures of toxicity Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)**

26,452.00 mg/kg

**ATEmix (dermal)**

7,466.00 mg/kg (ATE)

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Harmful to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Solvent naphtha (petroleum), light aliphatic 64742-89-8	72h EC50: = 4700 mg/L (Pseudokirchneriella subcapitata)			
Aromatic solvent 64742-95-6		96h LC50: = 9.22 mg/L (Oncorhynchus mykiss)		48h EC50: = 6.14 mg/L
Vinyl toluene 25013-15-4		96h LC50: = 23.4 mg/L (Pimephales rafinesque)		
Methyl ethyl ketoxime 96-29-7	72h EC50: = 83 mg/L (Desmodesmus subspicatus)	96h LC50: 777 - 914 mg/L (Pimephales promelas) 96h LC50: 320 - 1000 mg/L (Leuciscus idus) 96h LC50: = 760 mg/L (Poecilia reticulata)	EC50 = 281 mg/L 17 h EC50 = 950 mg/L 5 min	48h EC50: = 750 mg/L

**Persistence and Degradability**

No information available.

**Bioaccumulation**

Chemical Name	Log Pow
Vinyl toluene 25013-15-4	3.36
Methyl ethyl ketoxime 96-29-7	0.65

**Other adverse effects**

No information available.

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

<b>Disposal methods</b>	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
<b>Contaminated Packaging</b>	Do not reuse empty containers.
<b>US EPA Waste Number</b>	D001

**California Hazardous Waste Codes** 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

## 14. TRANSPORT INFORMATION

### DOT

<b>Proper Shipping Name</b>	CONSUMER COMMODITY
<b>Hazard Class</b>	ORM-D
<b>Description</b>	CONSUMER COMMODITY, ORM-D

### TDG

<b>UN-No.</b>	UN1866
<b>Proper Shipping Name</b>	RESIN SOLUTION
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Description</b>	UN1866, RESIN SOLUTION, 3, II, MARINE POLLUTANT

### MEX

<b>UN-No.</b>	UN1866
<b>Proper Shipping Name</b>	RESIN SOLUTION
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Description</b>	UN1866, RESIN SOLUTION, 3, II

### ICAO

<b>UN-No.</b>	UN1866
<b>Proper Shipping Name</b>	RESIN SOLUTION
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Description</b>	UN1866, RESIN SOLUTION, 3, II

### IATA

<b>UN-No.</b>	UN1866
<b>Proper Shipping Name</b>	RESIN SOLUTION
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Description</b>	UN1866, RESIN SOLUTION, 3, II

**IMDG/IMO**

UN-No.	UN1866
Proper Shipping Name	RESIN SOLUTION
Hazard Class	3
Packing Group	II
EmS-No.	F-E, S-E
Description	UN1866, RESIN SOLUTION, 3, II, (22°C C.C.), MARINE POLLUTANT

**RID**

UN-No.	UN1866
Proper Shipping Name	RESIN SOLUTION
Hazard Class	3
Packing Group	II
Classification code	F1
Description	UN1866, RESIN SOLUTION, 3, II

**ADR**

UN-No.	UN1866
Proper Shipping Name	RESIN SOLUTION
Hazard Class	3
Packing Group	II
Classification code	F1
Tunnel restriction code	(D/E)
Description	UN1866, RESIN SOLUTION, 3, II

**ADN**

UN-No.	UN1866
Proper Shipping Name	RESIN SOLUTION
Hazard Class	3
Packing Group	II
Classification code	F1
Special Provisions	640C
Description	UN1866, RESIN SOLUTION, 3, II
Hazard Labels	3
Limited Quantity	5 L
Ventilation	VE01

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**International Inventories**

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.
IECSC	-

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
---------------------	-----



<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	Yes
<b>Sudden release of pressure hazard</b>	No
<b>Reactive Hazard</b>	No

**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
2-Ethylhexanoic acid - 149-57-5	Developmental

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Titanium dioxide 13463-67-7	X	X	X		
Hydrous Alum Silicates 1332-58-7	X	X	X		
Vinyl toluene 25013-15-4	X	X	X		

**International Regulations**

**Mexico**

**National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Titanium dioxide 13463-67-7 ( 10 - 30 )		Mexico: TWA= 10 mg/m <sup>3</sup> Mexico: STEL= 20 mg/m <sup>3</sup>
Hydrous Alum Silicates 1332-58-7 ( 5 - 10 )		Mexico: TWA 10 mg/m <sup>3</sup> Mexico: STEL 20 mg/m <sup>3</sup>
Vinyl toluene 25013-15-4 ( 1 - 5 )		Mexico: TWA 50 ppm Mexico: TWA 240 mg/m <sup>3</sup> Mexico: STEL 100 ppm Mexico: STEL 485 mg/m <sup>3</sup>

Mexico - Occupational Exposure Limits - Carcinogens

**Canada**

**WHMIS Hazard Class**

Not determined

**16. OTHER INFORMATION**

**NFPA**                      **Health Hazards** 2    **Flammability** 3    **Instability** 0                      **Physical and Chemical Hazards** -



---

**HMIS**                      **Health Hazards** 2 \*   **Flammability** 3                      **Physical Hazard** 0   **Personal Protection**  
X

**Chronic Hazard Star Legend** \* = Chronic Health Hazard

**Prepared By**                      Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Revision Date**                      10-Jun-2015

**Revision Note**                      No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**