

SERIES 8901 MERCURY INTERIOR MOLD AND MILDEW AWAY



GENERAL PROPERTIES

A high performance acrylic interior paint formulated to protect interior surfaces while preventing mold & mildew growth on the paint film. Mercury Interior Mold And Mildew Away is designed to produce a tough, durable, washable finish that withstands moisture and resists dirt pick up.

It is suitable for application to interior walls, wall cavities, ceilings, trim, doors, and related paintable surfaces. It is excellent for use in bathrooms, basements, kitchens, laundry rooms, closets, locker rooms, hot tub rooms, enclosed porches and pool areas or any interior where mold & mildew is a concern. Mercury Interior Mold And Mildew Away can be used for commercial, industrial or residential use.

It is recommended for interior use on new or previously painted gypsum drywall, cured plaster, cement, poured concrete and stucco, concrete block, ceramic tile, primed or previously painted wood and metal, paneling, rigid paintable plastics, laminates, and other paintable surfaces.

DAMP SURFACES

May be applied over damp masonry walls but is not designed to stop active water leaks. Use Hydraulic Cement to patch active and non-active leaks, then waterproof with appropriate waterproofing paint for masonry prone to water intrusion. Mercury Interior Mold And Mildew Away may be used over any quality waterproofing paint to prevent mold and mildew growth on the paint film.

PRODUCT FEATURES

- Antimicrobial
- Self-priming
- Easy application, high-hide, excellent touch-up
- Durable, washable, dirt-resistant finish
- Tintable
- Low odor, fast-drying
- Soap and water clean-up

Resin Type	Water-based Acrylic
Pigment Type	Titanium Dioxide, Zinc Dioxide
Solvents	Water, Glycol, Ethers
Weight Per Gallon	11.6 lbs
Weight Per Liter	1.39 kg
% Solid by Weight	51%-57%
% Solid by Volume	38%-41%
VOC	<50 g/l
Recommended Dry Film by Coat	1.5 to 2.0 mils
Theoretical Coverage	300-400 sq. ft/ gal
Shelf Life	5 Years
Dry Time Average	To touch: 30 minutes To recoat: 2 hours
Packaged	One and five gallon pails
Flash Point	>200°F
Storage	40-80°F

Mercury

THINNING

Formulated to be used without thinning. If thinning is necessary (conventional spray applications), add no more than 10% by volume of fresh water

LIMITATIONS

Not intended for application to floors or any surface subject to immersion or prolonged contact with water including shower enclosures, saunas or steam rooms. Not recommended for use in HVAC duct work.

TINTING

Bright white but may be tinted to off-white, pastel or medium colors with a maximum of 4 ounces of universal colorant per gallon. Start with 75% of the tinting formula for a given color and adjust if necessary. Multiple containers of tinted paint should be intermixed (boxed) to ensure color uniformity. Shake or stir well before using.

DRY TIME

Dries to the touch in 30 minutes and can be recoated 2 hours after applying the first coat. Scrape resistance over glossy surfaces develops in 5 to 7 days. Do not scrub the new coating for seven days.

CLEAN UP

Clean up spills and paint drips with detergent and warm water. Wash application tools in detergent and warm water immediately use. If product has dried on application tools, soak overnight in a solution of equal parts household ammonia and water. Follow equipment manufacturer's directions to clean spray equipment. Dispose of unused or unwanted product in accordance with local laws regulating water-based coatings.

STORAGE

To prevent product from skinning over, dose container after each use. Keep lid tightly closed during storage. Protect from freezing. If contents freeze, thaw to room temperature before using.

ACCURACY OF DATA

The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit www.mercurypaint.com for the newest version of this data sheet.

WARRANTY

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor or other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.

