

SERIES 9900/9901

ACRYLIC LATEX TRAFFIC PAINT



PRODUCT FEATURES

- Quick dry
- Tough finish
- Weather resistant
- Abrasion resistant
- High visibility
- Excellent hiding

GENERAL PROPERTIES

A fast dry interior/ exterior high visibility, heavy-duty traffic paint.

RECOMMENDED USES

- Concrete
- Asphalt
- Curbs
- Parking lots
- Traffic aisles
- Storage areas

LIMITATIONS

- Do not apply when air and surface temperature are below 50°F.

Finish	Flat
Vehicle Type	100% Acrylic
Pigment Type	Durable pigment, lead & chromate free
Solvent Type	Water
Coating Category	Traffic Marking Coatings VOC 100 g/l max
% Solid by Weight	60% minimum
% Solid by Volume	40% minimum
Weight/Per Gallon	13 lbs / gal minimum
Recommended Dry Film by Coat	6.50-7.50 mils
Theoretical Coverage	300-345 lined ft/ gal @ 4 inches
Viscosity @ 77° F	80-95 KU
Dry Time Average	8 minutes @ 70°F
Application Method	Brush, roller, spray
Shelf Life	2 Years
Packaged	One and five gallon pails
Flash Point	N/A
Colors	Yellow, white, handicap blue & custom colors



SURFACE PREPARATION

All surfaces must be clean of dirt, grease, wax, foreign matter, peeling or chalky paint. Oil and grease have to be degreased.

APPLICATION CONDITIONS

Do not apply over moisture or wet surfaces.
Air and surface temperature must be above 50°F.

APPLICATION EQUIPMENT

Brush – Any good quality
Roller- Any good quality
Spray- Use stripping equipment

THINNING / CLEAN UP INSTRUCTIONS

Do not thin.

ENVIRONMENTAL INFORMATION

Contains no lead, mercury or chromate hazardous compounds. Complies with N.Y., N.J. and other states' requirements for limitation of volatile organic compounds. Meets New York Part 205 architectural surface coatings. Meets criteria for non-photochemical solvents in accordance with New York City Law 49.

Keep out of reach of children.

Safety Data Sheets available upon request.

Protect from freezing.

HEALTH & SAFETY INFORMATION

Use only with adequate ventilation. Do not breathe vapors, spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves.

RECOMMENDED SYSTEMS

Concrete	Finish: Series 9900/9901
Asphalt	Finish: Series 9900/9901

ACCURACY OF DATA

The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit www.mercurypaint.com for the newest version of this data sheet.

WARRANTY

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor of other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.

