SAFETY DATA SHEET

Issuing Date No data available **Revision Date** 19-May-2015 **Revision Number** 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name: SERIES 8000 LATEX SEMI GLOSS WHITE-COLORS

Other means of identification

Synonyms: None

Recommended use of the chemical and restrictions on use

Recommended Use: Paint, Latex

Uses advised against: No information available

Details of the supplier of the safety data sheet

Supplier Name: MERCURY PAINT

Supplier Address:
4808 FARRAGUT ROAD
BROOKLYN
NY
11203
US

Supplier Phone Number:
Phone:CHEMTREC18004249300
Fax:7184698787
Contact Phone7184698787 X160

Supplier Email: VGANDHI@MERCURYPAINT.COM

Emergency telephone number

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Gases)	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 4

GHS Label elements, including precautionary statements

Emergency Overview

Signal word Warning

Hazard Statements
Harmful if inhaled
Suspected of causing cancer
May cause respiratory irritation
Combustible liquid

Appearance Varies | Physical state Liquid | Odor No data available

Precautionary Statements - Prevention
Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep cool

Precautionary Statements - Response
IF exposed or concerned: Get medical advice/attention

Inhalation
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Fire
In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage
Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity
3.1487% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Harmful to aquatic life with long lasting effects
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals
No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

.

Chemical Name	CAS No	Weight-%	Trade Secret
Supplier Trade Secret	Proprietary	10 - 30	*
Titanium dioxide	13463-67-7	10 - 30	*
Limestone	1317-65-3	1 - 5	*
2,2,4-Trimethylpentane-1,3-diol monoisobutyrate	25265-77-4	1 - 5	*
Polyethylene glycol branched nonylphenyl ether	68412-54-4	0.1 - 1	*
Cyclohexane	110-82-7	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice	Show this safety data sheet to the doctor in attendance.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.
Skin contact	Wash with soap and water.
Inhalation	Remove to fresh air.
Ingestion	Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects	Coughing and/ or wheezing. Difficulty in breathing.

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media
CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical
Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray.

Uniform Fire Code	Irritant: Liquid Toxic: Liquid Combustible Liquid: III-B

Hazardous Combustion Products
Carbon oxides. Carbon monoxide. Carbon dioxide (CO_2).

Explosion Data

Sensitivity to Mechanical Impact	No.
Sensitivity to Static Discharge	Yes.

Protective equipment and precautions for firefighters
As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with eyes. Ensure adequate ventilation. Avoid breathing vapors or mists. Use personal protective equipment as required. Avoid generation of dust. Evacuate personnel to safe areas. See section 8 for more information. Take precautionary measures against static discharges. Do not touch or walk through spilled material.
Other Information	Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for containment	Prevent further leakage or spillage if safe to do so. Do not touch or walk through spilled material. Dike far ahead of liquid spill for later disposal.
Methods for cleaning up	Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling	Do not breathe dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities

Storage	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Store in accordance with the particular national regulations. Store in accordance with local regulations.
Incompatible Products	Acid chlorides. Acid anhydrides. Chloroformates. Strong oxidizing agents. Strong reducing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Supplier Trade Secret	STEL: 15 ppm	(vacated) TWA: 10 ppm	Ceiling: 4 ppm 15 min

	TWA: 10 ppm	(vacated) TWA: 30 mg/m^3 (vacated) STEL: 20 ppm (vacated) STEL: 60 mg/m^3	Ceiling: 15 mg/m^3 15 min
Titanium dioxide 13463-67-7	TWA: 10 mg/m^3	TWA: 15 mg/m^3 total dust (vacated) TWA: 10 mg/m^3 total dust	IDLH: 5000 mg/m^3
Limestone 1317-65-3	-	TWA: 15 mg/m^3 TWA: 5 mg/m^3 (vacated) TWA: 15 mg/m^3 (vacated) TWA: 5 mg/m^3	TWA: 5 mg/m^3 respirable dust TWA: 10 mg/m^3 total dust
Cyclohexane 110-82-7	TWA: 100 ppm	TWA: 300 ppm TWA: 1050 mg/m^3 (vacated) TWA: 300 ppm (vacated) TWA: 1050 mg/m^3	IDLH: 1300 ppm TWA: 300 ppm TWA: 1050 mg/m^3

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines — Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures — Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection — Tight sealing safety goggles.

Skin and body protection — Wear protective gloves and protective clothing.

Respiratory protection — No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures — Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state	Liquid		
Appearance	Varies	Odor	No data available
Color	No information available	Odor Threshold	No information available

Property	Values	Remarks Method
pH	8	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	93 C / 200 F	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	

Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	Soluble in water	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing properties	No data available	

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability
Stable under recommended storage conditions.
Possibility of Hazardous Reactions
None under normal processing.
Hazardous Polymerization
Hazardous polymerization does not occur.

Conditions to avoid
Excessive heat. Heat, flames and sparks.
Incompatible materials
Acid chlorides. Acid anhydrides. Chloroformates. Strong oxidizing agents. Strong reducing agents.
Hazardous Decomposition Products
Carbon oxides. Carbon monoxide. Carbon dioxide (CO2).

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information .

Inhalation	Specific test data for the substance or mixture is not available. Harmful by inhalation. (based on components). May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available.
Skin contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Supplier Trade Secret	= 2920 mg/kg (Rat)	= 2320 mg/kg (Rabbit)	= 11400 mg/m^3 (Rat) 4 h = 11.4 mg/L (Rat) 4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
2,2,4-Trimethylpentane-1,3-diol monoisobutyrate 25265-77-4	= 3200 mg/kg (Rat)	> 15200 mg/kg (Rat)	-
Polyethylene glycol branched nonylphenyl ether 68412-54-4	-	= 1780 µL/kg (Rabbit)	-
Cyclohexane 110-82-7	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 13.9 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms Coughing and/ or wheezing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Supplier Trade Secret	A3	Group 2B		X
Titanium dioxide 13463-67-7		Group 2B		X

ACGIH (American Conference of Governmental Industrial Hygienists)
A2 - Suspected Human Carcinogen
A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)
Group 1 - Carcinogenic to Humans
Group 2B - Possibly Carcinogenic to Humans
Group 3 - Not Classifiable as to Carcinogenicity in Humans
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Reproductive toxicity No information available.

STOT - single exposure Respiratory system.

STOT - repeated exposure No information available.

Chronic Toxicity No known effect based on information supplied. Contains a known or suspected carcinogen. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.

Target Organ Effects Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Lungs.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
7,782.00 mg/kg
ATEmix (dermal)
7,804.00 mg/kg (ATE)
ATEmix (inhalation-gas)
15,137.00 ppm (4 hr)
ATEmix (inhalation-dust/mist)
5.00 mg/l
ATEmix (inhalation-vapor)
37.00 ATEmix

12. ECOLOGICAL INFORMATION

Ecotoxicity
Harmful to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Supplier Trade Secret		96h LC50: = 14 mg/L (Pimephales promelas) 96h LC50: 15.04 - 21.54 mg/L (Lepomis macrochirus) 96h LC50: 26.1 - 36.63 mg/L (Poecilia reticulata)	EC50 = 2080 mg/L 5 min	24h EC50: = 52 mg/L
2,2,4-Trimethylpentane-1,3-diol monoisobutyrate 25265-77-4	72h EC50: = 18.4 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 30 mg/L (Pimephales promelas)		96h LC50: > 95 mg/L
Cyclohexane 110-82-7	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: 23.03 - 42.07 mg/L (Pimephales promelas) 96h LC50: 24.99 - 44.69 mg/L (Lepomis macrochirus) 96h LC50: 48.87 - 68.76 mg/L (Poecilia reticulata) 96h LC50: 3.96 - 5.18 mg/L (Pimephales promelas)	EC50 = 85.5 mg/L 5 min EC50 = 93 mg/L 10 min	24h EC50: > 400 mg/L

Persistence and Degradability
No information available.

Bioaccumulation

Chemical Name	Log Pow
Supplier Trade Secret	0.73
2,2,4-Trimethylpentane-1,3-diol monoisobutyrate 25265-77-4	3.47
Cyclohexane 110-82-7	3.44

Other adverse effects
No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods: This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging: Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number: U056

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Cyclohexane 110-82-7				U056

California Hazardous Waste Codes: 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Supplier Trade Secret	Toxic Ignitable
Cyclohexane 110-82-7	Toxic

14. TRANSPORT INFORMATION

DOT: NOT REGULATED
- Proper Shipping Name: NON REGULATED
- Hazard Class: N/A

TDG: Not regulated

MEX: Not regulated

ICAO: Not regulated

IATA: Not regulated
- Proper Shipping Name: NON REGULATED
- Hazard Class: N/A

IMDG/IMO: Not regulated
- Hazard Class: N/A

RID: Not regulated

ADR: Not regulated

ADN: Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Supplier Trade Secret -		10 - 30	0.1
Cyclohexane - 110-82-7	110-82-7	0.1 - 1	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Supplier Trade Secret	5000 lb			X
Cyclohexane 110-82-7	1000 lb			X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Supplier Trade Secret	5000 lb	5000 lb	RQ 5000 lb final RQ RQ 2270 kg final RQ
Cyclohexane 110-82-7	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Ethyl alcohol - 64-17-5	Carcinogen Developmental
Formaldehyde - 50-00-0	Carcinogen

U.S. State Right-to-Know Regulations

.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Supplier Trade Secret	X	X	X	X	X
Titanium dioxide 13463-67-7	X	X	X		
Limestone 1317-65-3	X	X	X		
Petroleum distillates, solvent-refined light paraffinic 64741-89-5		X			
Cyclohexane 110-82-7	X	X	X	X	

International Regulations

Mexico
National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Supplier Trade Secret (10 - 30)	A3	Mexico: TWA 10 ppm Mexico: TWA 30 mg/m^3 Mexico: STEL 20 ppm Mexico: STEL 60 mg/m^3
Titanium dioxide 13463-67-7 (10 - 30)		Mexico: TWA= 10 mg/m^3 Mexico: STEL= 20 mg/m^3
Limestone 1317-65-3 (1 - 5)		Mexico: TWA= 10 mg/m^3 Mexico: STEL= 20 mg/m^3
Cyclohexane 110-82-7 (0.1 - 1)		Mexico: TWA 300 ppm Mexico: TWA 1050 mg/m^3 Mexico: STEL 375 ppm Mexico: STEL 1300 mg/m^3

Mexico - Occupational Exposure Limits - Carcinogens
A3 - Confirmed Animal Carcinogen

16. OTHER INFORMATION

NFPA	Health Hazards	2	Flammability	2	Instability	0	Physical and Chemical Hazards -
HMIS	Health Hazards	2 *	Flammability	2	Physical Hazard	0	Personal Protection X

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501
Revision Date	19-May-2015
Revision Note	No information available

Disclaimer
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet