

SERIES 6800

ALKYD PRIMER/ SEALER/ STAIN BLOCKER ZOOM ACTION BLOCKER



PRODUCT FEATURES

- Quick dry- 20 minutes
- Hi-hiding
- Odorless
- Topcoat with Alkyd or Water-based
- Stain blocker
- Excellent for smoke and nicotine stains

GENERAL PROPERTIES

A heavy duty interior/ exterior, odorless primer/ sealer/stain blocker. Provides a smooth well sealed surface with excellent film build and enamel holdout. Premium quality primer to be used under wallpaper.

RECOMMENDED USES

- Wood
- Metal
- Drywall
- Concrete
- Masonry
- Plaster

LIMITATIONS

- Do not apply when air and surface temperature is below 45°F.
- Do not use on galvanized metal.

Finish	Low Luster
Vehicle Type	Odorless Alkyd
Pigment Type	Titanium Dioxide
Solvent Type	Odorless Solvent
Coating Category	Speciality primer, sealer, undercoater max VOC 350 g/l
% Solid by Weight	75% minimum
% Solid by Volume	55% minimum
Weight/Per Gallon	12.60 lbs/gal avg
Recommended Dry Film by Coat	1.5 to 2 mils per coat
Theoretical Coverage	400-475 sq ft. / gallon
Viscosity @ 77° F	85-95 KU
Dry Time Average	To touch: 20 min To reocat: 40 min
Application Method	Brush, roller, spray
Shelf Life	2 Years
Packaged	One, two and five gallon pails
Flash Point	104°F
Colors	White and tinted colors upon request





APPLICATION CONDITIONS

Do not apply over moisture or wet surfaces.
Air and surface temperature must be above 45°F.
Relative humidity: 70%

APPLICATION EQUIPMENT

Brush – Good quality china bristle
Roller – Short nap roller
Spray – Fluid pressure 1,500-2,000 PSI
Tip- 0.18 orifice

THINNING / CLEAN UP INSTRUCTIONS

Do not thin. Clean up with Mercury odorless thinner.

ENVIRONMENTAL INFORMATION

Contains no lead, mercury or chromate hazardous compounds. Complies with N.Y., N.J. and other states' requirements for limitation of volatile organic compounds. Meets New York Part 205 architectural surface coatings. Meets criteria for non-photochemical solvents in accordance with New York City Law 49.

Keep out of reach of children.
Material Safety Data Sheets available upon request.
Keep from freezing.

HEALTH & SAFETY INFORMATION

WARNING: COMBUSTIBLE LIQUID AND VAPOR.
Vapor harmful. Causes eye, skin, nose and throat irritation. Keep away from heat and open flame.
To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHATC23C or equivalent), or leave the area. Close container after each use. Avoid prolonged contact with skin. Do not take internally. If swallowed, contact a physician or poison control center. Avoid skin contact.

RECOMMENDED SYSTEMS

Plaster/ Drywall New	Primer: Series 6800 Finish: appropriate Mercury Finish Coat
Plaster/ Drywall Repainted	Primer: Series 6800 Finish: appropriate Mercury Finish Coat
Wood New/ Repainted	Primer: Series 6800 Finish: appropriate Mercury Finish Coat
Masonry New/ Repainted	Primer: Series 6800 Finish: appropriate Mercury Finish Coat
Metal Surfaces	Primer: Series 6800 Finish: appropriate Mercury Finish Coat

ACCURACY OF DATA

The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit www.mercurypaint.com for the newest version of this data sheet.

WARRANTY

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor of other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.

